According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

ersion .1	Revision Date: 04/07/2020		DS Number: 0001030776	Print Date: 04/08/2020 Date of last issue: 01/24/2019
ECTION	1. IDENTIFICATION			
Produ	uct name	:	Shell Rotella T6	5W-40
Produ	uct code	:	001D5438	
Manu	ifacturer or supplier's	deta	ails	
Manu	facturer/Supplier	:	Shell Oil Produ PO Box 4427 Houston TX 77 USA	
	Request omer Service	:	(+1) 877-276-72	285
Spill I	rgency telephone nun nformation h Information	:	877-504-9351 877-242-7400	
	mmended use of the mmended use		nical and restrict Engine oil.	ions on use
ECTION	2. HAZARDS IDENTI		ΓΙΟΝ	
GHS	classification in acco	rdan	ce with 29 CFR 1	910.1200
Long- hazar	term (chronic) aquatic d	:	Category 3	
GHS	label elements			
Haza	rd pictograms	:	No symbol	
Signa	l word	:	No signal word	
Haza	rd statements	:	HEALTH HAZAI Not classified as ENVIRONMEN	a physical hazard under GHS criteria. RDS: a health hazard under GHS criteria. FAL HAZARDS:
Drees				aquatic life with long lasting effects.
Preca	autionary statements	:	Prevention: P273 Avoid rele	aquatic life with long lasting effects.
Pieca	autionary statements	:	Prevention:	ase to the environment.

No precautionary phrases.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Version	Revision Date:	SDS Number:
2.1	04/07/2020	800001030776

Print Date: 04/08/2020 Date of last issue: 01/24/2019

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

 Synthetic base oil and additives. Highly refined mineral oil. The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346. The highly refined mineral oil is only present as additive diluent.

* contains one or more of the following CAS-numbers: 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9, 68649-12-7, 151006-60-9, 163149-28-8.

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *		Not Assigned	0 - 90
Alkaryl amine	bis(nonylphenyl)amine	36878-20-3	1 - 5
Alkyl borate		Not Assigned	0.1 - 0.99
Dialkyl alkaryl ami- nomethyl dicarbox- ylate		Not Assigned	0.1 - 0.99
Calcium sulphonate	Benzenesul- fonic acid, mono-C16-24- alkyl derivs., calcium salts	70024-69-0	0.1 - 0.99

SECTION 4. FIRST-AID MEASURES

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Version 2.1	Revision Date: 04/07/2020		DS Number: 00001030776	Print Date: 04/08/2020 Date of last issue: 01/24/2019
In cas	e of eye contact	:	Remove contact I rinsing.	pious quantities of water. enses, if present and easy to do. Continue ion occurs, obtain medical attention.
lf swa	llowed	:	0	tment is necessary unless large quantities owever, get medical advice.
	mportant symptoms ffects, both acute and ed	:	of black pustules	s signs and symptoms may include formation and spots on the skin of exposed areas. sult in nausea, vomiting and/or diarrhoea.
Protec	ction of first-aiders	:		ng first aid, ensure that you are wearing the nal protective equipment according to the d surroundings.
medic	tion of any immediate al attention and special nent needed	:	Treat symptomati	cally.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.	
Environmental precautions		Local authorities should be advised if significant spillages	

Environmental precautions : Local authorities should be advised if significant spillages

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Vers 2.1	sion	Revision Date: 04/07/2020		S Number: 0001030776	Print Date: 04/08/2020 Date of last issue: 01/24/2019	
		s and materials for ment and cleaning up	:	cannot be contained. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or othe suitable material and dispose of properly.		
	Additior	nal advice	:	see Chapter 8 of 1	election of personal protective equipment his Safety Data Sheet. lisposal of spilled material see Chapter 13 of heet.	

SECTION 7. HANDLING AND STORAGE

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Further information on stor- age stability	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Version	Revision Date:	SDS Number:	Print Date: 04/08/2020
2.1	04/07/2020	800001030776	Date of last issue: 01/24/2019

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	-	TWA (Inhal-	5 mg/m3	ACGIH
		able particu-	-	
		late matter)		

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	:	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
		General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or mainte-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Version 2.1	Revision Date: 04/07/2020	SDS Number: 800001030776	Print Date: 04/08/2020 Date of last issue: 01/24/2019
		subsequent rec Always observe washing hands drinking, and/or protective equip	good personal hygiene measures, such as after handling the material and before eating, smoking. Routinely wash work clothing and ment to remove contaminants. Discard con- ng and footwear that cannot be cleaned.
Pers	onal protective equip	ment	
	biratory protection	: No respiratory p conditions of us In accordance w tions should be If engineering c tions to a level w select respirator cific conditions of Check with resp Where air-filterin priate combinat Select a filter su	with good industrial hygiene practices, precau- taken to avoid breathing of material. ontrols do not maintain airborne concentra- which is adequate to protect worker health, ry protection equipment suitable for the spe- of use and meeting relevant legislation. biratory protective equipment suppliers. ng respirators are suitable, select an appro- tion of mask and filter. hitable for the combination of organic gases d particles [Type A/Type P boiling point
	d protection emarks	gloves approved US: F739) made suitable chemic gloves Suitabilit usage, e.g. freq sistance of glov glove suppliers. Personal hygier Gloves must on gloves, hands s cation of a non- For continuous through time of 480 minutes wh short-term/splas recognize that s may not be ava time maybe acc and replacemer a good predicto dependent on th Glove thickness	htact with the product may occur the use of d to relevant standards (e.g. Europe: EN374, e from the following materials may provide al protection. PVC, neoprene or nitrile rubber y and durability of a glove is dependent on uency and duration of contact, chemical re- e material, dexterity. Always seek advice from Contaminated gloves should be replaced. he is a key element of effective hand care. ly be worn on clean hands. After using hould be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. contact we recommend gloves with break- more than 240 minutes with preference for > ere suitable gloves can be identified. For sh protection we recommend the same but suitable gloves offering this level of protection ilable and in this case a lower breakthrough eptable so long as appropriate maintenance at regimes are followed. Glove thickness is not r of glove resistance to a chemical as it is ne exact composition of the glove material. a should be typically greater than 0.35 mm he glove make and model.
Eye	protection	: If material is ha	ndled such that it could be splashed into eyes,

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Version 2.1	Revision Date: 04/07/2020	SDS Number: 800001030776	Print Date: 04/08/2020 Date of last issue: 01/24/2019
		protective e	yewear is recommended.
Skin	and body protection	work clothes	ion is not ordinarily required beyond standard s. actice to wear chemical resistant gloves.
Prote	ctive measures		otective equipment (PPE) should meet recom- ional standards. Check with PPE suppliers.
Therr	Thermal hazards		ble
Envii	ronmental exposure c	ontrols	
Gene	eral advice	vant enviror of the enviror necessary, p charged to v municipal or discharge to Local guidel	briate measures to fulfill the requirements of rele- mental protection legislation. Avoid contamination onment by following advice given in Section 6. If prevent undissolved material from being dis- waste water. Waste water should be treated in a industrial waste water treatment plant before o surface water. ines on emission limits for volatile substances served for the discharge of exhaust air containing

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquid at room temperature.
Colour	:	amber
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	-42 °C / -44 °F Method: ASTM D97
Initial boiling point and boiling range	:	> 280 °C / 536 °F estimated value(s)
Flash point	:	224 °C / 435 °F
		Method: ASTM D92 (COC)
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit / upper flammability limit	:	Typical 10 %(V)
Lower explosion limit / Lower	:	Typical 1 %(V)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Version 2.1	Revision Date: 04/07/2020		S Number: 0001030776	Print Date: 04/08/2020 Date of last issue: 01/24/2019
flam	mability limit			
Vapo	our pressure	:	< 0.5 Pa (20 °C)	/ 68 °F)
			estimated value	(s)
Rela	tive vapour density	:	> 1 estimated value((s)
Rela	tive density	:	0.858 (15 °C / 59	9°F)
Dens	sity	:	858 kg/m3 (15.0 Method: ASTM I	
	bility(ies) /ater solubility	:	negligible	
S	olubility in other solvents	:	Data not availab	le
	tion coefficient: n- nol/water	:		nation on similar products)
Auto	-ignition temperature	:	> 320 °C / 608 °	F
Deco	omposition temperature	:	Data not availab	le
Visc V	osity iscosity, dynamic	:	Data not availab	le
V	iscosity, kinematic	:	87 mm2/s (40.0	°C / 104.0 °F)
			Method: ASTM I	D445
			14.2 mm2/s (100) °C / 212 °F)
			Method: ASTM [D445
Expl	osive properties	:	Not classified	
Oxid	izing properties	:	Data not availab	le
Cond	ductivity	:	This material is r	not expected to be a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Version 2.1	Revision Date: 04/07/2020	SDS Number: 800001030776	Print Date: 04/08/2020 Date of last issue: 01/24/2019	
Cond	litions to avoid	: Extremes of te	emperature and direct sunlight.	
Incompatible materials		: Strong oxidisir	ng agents.	
Hazardous decomposition products		: No decompos	ition if stored and applied as directed.	
Haza	rdous decomposition	: No decompos		

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise,
		the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Version	Revision Date:	SDS Number:	Print Date: 04/08/2020
2.1	04/07/2020	800001030776	Date of last issue: 01/24

Date of last issue: 01/24/2019

Alkyl borate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Dialkyl alkaryl aminomethyl dicarboxylate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Calcium sulphonate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Reproductive toxicity	
Product:	
	Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.
STOT - single exposure	
Product:	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Version	Revision Date:	SDS Number:	Print
2.1	04/07/2020	800001030776	Date

Print Date: 04/08/2020 Date of last issue: 01/24/2019

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment :	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity	
Product: Toxicity to fish (Acute toxici- : ty)	Remarks: LL/EL/IL50 10-100 mg/l Harmful
Toxicity to daphnia and other : aquatic invertebrates (Acute toxicity)	Remarks: LL/EL/IL50 10-100 mg/l Harmful
Toxicity to algae (Acute tox- : icity)	Remarks: LL/EL/IL50 10-100 mg/l Harmful
Toxicity to fish (Chronic tox- : icity)	Remarks: NOEC/NOEL > 10 - <=100 mg/l

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Versio 2.1	on	Revision Date: 04/07/2020		9S Number: 0001030776	Print Date: 04/08/2020 Date of last issue: 01/24/2019
а		to daphnia and other invertebrates (Chron- y)	:	Remarks: NOEC/I	NOEL > 10 - <=100 mg/l
		to microorganisms oxicity)	:	Remarks: NOEC/I	NOEL > 10 - <=100 mg/l
F	Persist	ence and degradabili	ity		
	Produc Biodegr	<u>t:</u> adability	:	Major constituents	dily biodegradable. are inherently biodegradable, but contains nay persist in the environment.
E	Bioacc	umulative potential			
-	Produc Bioaccu	<u>t:</u> Imulation	:	Remarks: Contain cumulate.	s components with the potential to bioac-
Ν	Mobility	y in soil			
	Produc			Pomorko: Liquidu	inder meet environmental conditions
N	Vobility		:	Adsorbs to soil an	inder most environmental conditions. d has low mobility
				Remarks: Floats of	on water.
c	Other a	dverse effects			
<u>F</u>	Produc	<u>t:</u>			
	Additior nation	al ecological infor-	:	ozone creation po Product is a mixtu	one depletion potential, photochemical tential or global warming potential. re of non-volatile components, which will not in any significant quantities under normal
				Poorly soluble mix Causes physical f	cture. ouling of aquatic organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Version	Revision Date:	SDS Number:	Print Date: 04/08/2020
2.1	04/07/2020	800001030776	Date of last issue: 01/24/2019
Contaminated packaging		ground water, or Waste, spills or Dispose in accor to a recognized the collector or o Disposal should	hould not be allowed to contaminate soil or be disposed of into the environment. used product is dangerous waste. rdance with prevailing regulations, preferably collector or contractor. The competence of contractor should be established beforehand. be in accordance with applicable regional, cal laws and regulations.
Local	l legislation	•	be in accordance with applicable regional,
Rema	arks		al laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
toluene	108-88-3	100	100 (F005)
2-methylpropan-1-ol	78-83-1	100	100 (F005)
benzene	71-43-2	10	10 (D018)
Ethylbenzene	100-41-4	100	100 (F003)
benzene	71-43-2	10	*

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Version	Revision Date:	SDS Number:	Print Date: 04/08/2020
2.1	04/07/2020	800001030776	Date of last issue: 01/24/2019

*: Calculated RQ exceeds reasonably attainable upper limit., The components with RQs are given for information., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	: No SARA Hazards
SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Naphthalene	91-20-3	0.0002 %
Ethylbenzene	100-41-4	0.0002 %
benzene	71-43-2	0.0002 %
toluene	108-88-3	0.0002 %

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Polyolefin	68649-12-7
Zinc dialkyl dithiophosphate	84605-29-8
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0

California Prop. 65

WARNING: This product can expose you to chemicals including benzene, Ethylbenzene, Naphthalene, which is/are known to the State of California to cause cancer, and benzene, toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Polyolefin	68649-12-7

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EINECS	:	Notified with Restrictions.
TSCA	:	All components listed.
DSL	:	All components listed.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Number:

Shell Rotella T6 5W-40

Version	Revision Date:	SDS Number:
2.1	04/07/2020	800001030776

Print Date: 04/08/2020 Date of last issue: 01/24/2019

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac-0, 1, 0 tivity)

Full text of other abbreviations

ACGIH OSHA Z-1 ACGIH / TWA OSHA Z-1 / TWA Abbreviations and Acronyms		USA. ACGIH Threshold Limit Values (TLV) USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants 8-hour, time-weighted average 8-hour time weighted average The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
		ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level DNEL = Derived No Effect Level DSL = Canada Domestic Substance List EC = European Commission EC50 = Effective Concentration fifty ECETOC = European Chemicals Agency EINECS = The European Inventory of Existing Commercial Chemical Substances EL50 = Effective Loading fifty ENCS = Japanese Existing and New Chemical Substances Inventory EWC = European Waste Code GHS = Globally Harmonised System of Classification and Labelling of Chemicals IARC = International Agency for Research on Cancer IATA = International Agency for Research on Cancer

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 5W-40

Version	Revision Date:	SDS Number:	Print Date: 04/08/2020
2.1	04/07/2020	800001030776	Date of last issue: 01/24/2019
		determination of KECI = Korea E LC50 = Lethal O LD50 = Lethal O LL/EL/IL = Leth LL50 = Lethal L MARPOL = Inter Pollution From T NOEC/NOEL = served Effect Lo OE_HPV = Occo PBT = Persister PICCS = Philipp Substances PNEC = Predic REACH = Regis Chemicals RID = Regulatio gerous Goods b SKIN_DES = S STEL = Short te TRA = Targeted TSCA = US To TWA = Time-W	ernational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob- evel cupational Exposure - High Production Volume nt, Bioaccumulative and Toxic pine Inventory of Chemicals and Chemical ted No Effect Concentration stration Evaluation And Authorisation Of ons Relating to International Carriage of Dan- by Rail

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
Revision Date	:	04/07/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN