According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

Version	Revision Date:	SDS Number:	Print Date: 02/18/2023
2.1	02/17/2023	800010027938	Date of last issue: 08/12/2022

SECTION 1. IDENTIFICATION

Product name : Shell Rotella T3 Fleet 15W-40

Product code : 001F8881

Manufacturer or supplier's details

Manufacturer/Supplier	: Shell Oil Products US PO Box 4427 Houston TX 77210-4427 USA
SDS Request	: (+1) 877-276-7285
Customer Service	:

Emergency telephone number

Spill Information	:	877-242-7400
Health Information	:	877-504-9351

Recommended use of the chemical and restrictions on use

Recommended use : Engine oil.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements Hazard pictograms	:	No Hazard Symbol required
Signal word	:	No signal word
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	:	Prevention: No precautionary phrases. Response: No precautionary phrases. Storage: No precautionary phrases.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

Version	Revision Date:
2.1	02/17/2023

SDS Number: 800010027938 Print Date: 02/18/2023 Date of last issue: 08/12/2022

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature	 Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regula- tion (EC) 1272/2008, Annex VI, Part 3, Note L).
	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-

68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4, 64741-89-5.

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *		Not Assigned	0 - 90
Alkaryl amine	bis(nonylphenyl)amine	36878-20-3	0-5
Alkylated phenol ester		125643-61-0	0 - 3
Zinc dialkyl dithio- phosphate	Phosphorodi- thioic acid, mixed O,O- bis(1,3- dimethylbutyl and iso-Pr) esters, zinc salts	84605-29-8	0 - 1.99
Zinc dialkyldithio- phosphate	Phosphorodi- thioic acid, mixed O,O- bis(sec-Bu and isooctyl) esters, zinc salts	113706-15-3	0 - 1.99

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

Version	Revision Date:	SDS Number:	Print Date: 02/18/2023
2.1	02/17/2023	800010027938	Date of last issue: 08/12/2022

Calcium alkaryl sul- phonate	Benzene, poly- propene derivs., sul- fonated, calci- um salts	75975-85-8	0 - 0.99
Calcium sulphonate	Benzenesul- fonic acid, mono-C16-24- alkyl derivs., calcium salts	70024-69-0	0 - 0.99

SECTION 4. FIRST-AID MEASURES					
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.			
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.			
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.			
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.			
Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.			
Indication of any immediate medical attention and special treatment needed	:	Treat symptomatically.			

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

Vers 2.1	sion	Revision Date: 02/17/2023		0S Number: 0010027938	Print Date: 02/18/2023 Date of last issue: 08/12/2022
	ods	c extinguishing meth- l protective equipment ighters	:	cumstances and t Proper protective gloves are to be w large contact with Breathing Apparate a confined space.	measures that are appropriate to local cir- he surrounding environment. equipment including chemical resistant yorn; chemical resistant suit is indicated if spilled product is expected. Self-Contained tus must be worn when approaching a fire in Select fire fighter's clothing approved to s (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk as- sessment of local circumstances to help determine appropri- ate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

Version 2.1	Revision Date: 02/17/2023		DS Number: 00010027938	Print Date: 02/18/2023 Date of last issue: 08/12/2022
Avoi	dance of contact	:	Strong oxidising a	agents.
Prod	luct Transfer	:		and bonding procedures should be used nsfer operations to avoid static accumulation.
	ner information on stor- stability	:	place.	ghtly closed and in a cool, well-ventilated
			Store at ambient	temperature.
Pack	aging material	:	Suitable material: steel or high dens Unsuitable mater	
Cont	ainer Advice	:		tainers should not be exposed to high tem- e of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-		
		late matter)		

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures : The level of protection and types of controls necessary will

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 2.1	Revision Date: 02/17/2023	SDS Number: 800010027938	Print Date: 02/18/2023 Date of last issue: 08/12/2022
		controls based Appropriate m	g upon potential exposure conditions. Select on a risk assessment of local circumstances. easures include: ilation to control airborne concentrations.
			I is heated, sprayed or mist formed, there is al for airborne concentrations to be generated.
		controls. Educate and tr measures rele product. Ensure approp equipment use equipment, loc Drain down sy nance. Retain drain do subsequent re Always observ washing hands drinking, and/o	ures for safe handling and maintenance of rain workers in the hazards and control vant to normal activities associated with this priate selection, testing and maintenance of ed to control exposure, e.g. personal protective rai exhaust ventilation. stem prior to equipment break-in or mainte- powns in sealed storage pending disposal or cycle. e good personal hygiene measures, such as a after handling the material and before eating, or smoking. Routinely wash work clothing and pment to remove contaminants. Discard con- ning and footwear that cannot be cleaned.
Perso	onal protective equip	oment	
	iratory protection	: No respiratory conditions of u In accordance tions should be If engineering tions to a level select respirate cific conditions Check with res Where air-filter priate combina Select a filter s	with good industrial hygiene practices, precau- e taken to avoid breathing of material. controls do not maintain airborne concentra- which is adequate to protect worker health, ory protection equipment suitable for the spe- of use and meeting relevant legislation. spiratory protective equipment suppliers. ring respirators are suitable, select an appro- tion of mask and filter. suitable for the combination of organic gases and particles [Type A/Type P boiling point
	protection emarks	gloves approve US: F739) mad suitable chemi gloves Suitabil usage, e.g. fre	ontact with the product may occur the use of ed to relevant standards (e.g. Europe: EN374, de from the following materials may provide cal protection. PVC, neoprene or nitrile rubber ity and durability of a glove is dependent on quency and duration of contact, chemical re- ve material, dexterity. Always seek advice from

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 2.1	Revision Date: 02/17/2023		lumber: 0027938	Print Date: 02/18/2023 Date of last issue: 08/12/2022
		Pe Gli glo ca Fo thr 48 sh rea tim an de Gli	rsonal hygie oves must or oves, hands s tion of a non r continuous ough time of 0 minutes will ort-term/spla cognize that ay not be avail the maybe acc d replaceme good predictor pendent on to ove thicknes	A. Contaminated gloves should be replaced. ne is a key element of effective hand care. hly be worn on clean hands. After using should be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. contact we recommend gloves with break- more than 240 minutes with preference for > here suitable gloves can be identified. For sh protection we recommend the same but suitable gloves offering this level of protection ailable and in this case a lower breakthrough ceptable so long as appropriate maintenance nt regimes are followed. Glove thickness is not or of glove resistance to a chemical as it is he exact composition of the glove material. s should be typically greater than 0.35 mm he glove make and model.
Eye p	protection			andled such that it could be splashed into eyes, vear is recommended.
Skin	and body protection	wo	ork clothes.	is not ordinarily required beyond standard ice to wear chemical resistant gloves.
Prote	ective measures			ctive equipment (PPE) should meet recom- al standards. Check with PPE suppliers.
Therr	mal hazards	: No	t applicable	
Envir	ronmental exposure o	ontrols		
Gene	eral advice	va of ch mu dis Lo	nt environme the environm cessary, pre arged to was unicipal or in charge to su cal guideline	te measures to fulfill the requirements of rele- ental protection legislation. Avoid contamination nent by following advice given in Section 6. If vent undissolved material from being dis- ste water. Waste water should be treated in a dustrial waste water treatment plant before urface water. s on emission limits for volatile substances ved for the discharge of exhaust air containing
SECTION	9. PHYSICAL AND C	HEMICA	- PROPERT	IES
Appe	arance	: lic	quid	
Colou	ır	: ai	nber	
Odou	ır	: D	ata not availa	able
Odou	ır Threshold	: D	ata not availa	able
pН		: N	ot applicable	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Vers 2.1	sion	Revision Date: 02/17/2023		S Number: 010027938	Print Date: 02/18/2023 Date of last issue: 08/12/2022
	pour po	bint	:	-35 °C / -31 °F Method: ASTM D	5950
	Initial b range	oiling point and boiling	:	> 280 °C / 536 °F estimated value(s	
	Flash p	point	:	236 °C / 457 °F	
				Method: ASTM D	92 (COC)
	Evapor	ation rate	:	Data not available	e
	Flamm Flar	ability nmability (solid, gas)	:	Not applicable	
	Flar	nmability (liquids)	:	Not classified as	flammable but will burn.
	Upp	explosion limit and upp per explosion limit / up- flammability limit			imability limit
		ver explosion limit / ver flammability limit	:	Typical 1 %(V)	
	Vapour	pressure	:	< 0.5 Pa (20 °C /	68 °F)
				estimated value(s	3)
	Relativ	e vapour density	:	> 5	
	Relativ	e density	:	0.876 (15 °C / 59	°F)
	Density	/	:	876 kg/m3 (15.0 Method: ASTM D	
	Solubili Wat	ity(ies) ter solubility	:	negligible	
	Solu	ubility in other solvents	:	Data not available	e
	Partitio octanol	n coefficient: n- l/water	:	log Pow: > 6 (based on inform	ation on similar products)
	Auto-ig	nition temperature	:	> 320 °C / 608 °F	
	Decom	position temperature	:	Data not available	e
	Viscosi Visc	ty cosity, dynamic	:	Data not available	e
	Visc	cosity, kinematic	:	115 mm2/s (40.0	°C / 104.0 °F)
				Method: ASTM D	445

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

/ersion 2.1	Revision Date: 02/17/2023		S Number: 010027938	Print Date: 02/18/2023 Date of last issue: 08/12/2022
			15.3 mm2/s (1	00 °C / 212 °F)
			Method: ASTM	D445
Explo	sive properties	:	Classification (Code: Not classified
Oxidi	zing properties	:	Data not availa	ble
Cond	uctivity	:	This material is	not expected to be a static accumulator.
SECTION Reac	10. STABILITY AND RE	EAC [.]	The product do	bes not pose any further reactivity hazards in se listed in the following sub-paragraph.
Chem	nical stability	:	Stable.	se listed in the following sub-paragraph.
Possi tions	bility of hazardous reac-	:	Reacts with str	ong oxidising agents.
Cond	itions to avoid	:	Extremes of te	mperature and direct sunlight.
Incon	npatible materials	:	Strong oxidisin	g agents.
Haza	rdous decomposition	:	No decomposit	tion if stored and applied as directed.

Basis for assessment	: Information given is based on data on the components and	
	the toxicology of similar products.Unless indicated otherwise,	
	the data presented is representative of the product as a	
	whole, rather than for individual component(s).	
	,	

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:		
Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

Version	Revision Date:	SDS Number:	Ρ
2.1	02/17/2023	800010027938	D

Print Date: 02/18/2023 Date of last issue: 08/12/2022

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Components:

Zinc dialkyl dithiophosphate: Remarks: Based on available data, the classification criteria are not met.

Zinc dialkyldithiophosphate: Remarks: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

Calcium alkaryl sulphonate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Calcium sulphonate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Germ cell mutagenicity

Product:

Genotoxicity in vivo

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

Version 2.1	Revision Date: 02/17/2023	SDS Number: 800010027938	Print Date: 02/18/2023 Date of last issue: 08/12/2022		
IARC		•	s product present at levels greater than or ntified as probable, possible or confirmed by IARC.		
OSHA	λ.	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.			
NTP		•	s product present at levels greater than or ntified as a known or anticipated carcinogen		
Repro Produ	ductive toxicity ct:				
	s on fertility		levelopmental toxicant., Does not impair n available data, the classification criteria are		

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 2.1	Revision Date: 02/17/2023		0S Number: 0010027938	Print Date: 02/18/2023 Date of last issue: 08/12/2022
Bas	Basis for assessment		Ecotoxicological data have not been determined specifi for this product. Information given is based on a knowledge of the comp and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is repre tive of the product as a whole, rather than for individual ponent(s).(LL/EL/IL50 expressed as the nominal amoun product required to prepare aqueous test extract).	
Eco	otoxicity			
	duct: icity to fish (Acute toxici-	:	Remarks: Based of are not met. Practically non tox LL/EL/IL50 > 100	
	icity to daphnia and other atic invertebrates (Acute city)	:	Remarks: Based of are not met. Practically non toy LL/EL/IL50 > 100	
Tox icity	icity to algae (Acute tox-)	:	Remarks: Based of are not met. Practically non toy LL/EL/IL50 > 100	
Tox icity	icity to fish (Chronic tox-	:	Remarks: Based of are not met.	on available data, the classification criteria
aqu	icity to daphnia and other atic invertebrates (Chron- pxicity)	:	Remarks: Based of are not met.	on available data, the classification criteria
	icity to microorganisms ute toxicity)	:	Remarks: Based of are not met.	on available data, the classification criteria
Per	sistence and degradabili	ty		
	<u>duct:</u> degradability	:	Major constituents components that in Persistent per IMO International Oil P tion: "A non-persis consists of hydroc by volume, distills at least 95% of wh	rollution Compensation (IOPC) Fund defini- stent oil is oil, which, at the time of shipment, carbon fractions, (a) at least 50% of which, at a temperature of 340°C (645°F) and (b) nich, by volume, distils at a temperature of en tested by the ASTM Method D-86/78 or

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

Version 2.1	Revision Date: 02/17/2023		0S Number: 0010027938	Print Date: 02/18/2023 Date of last issue: 08/12/2022
Bioad	ccumulative potential	I		
Prod	uct:			
-	cumulation	:	Remarks: Cont cumulate.	ains components with the potential to bioac-
Mobi	lity in soil			
Prod	uct:			
Mobil	Mobility			d under most environmental conditions. it will adsorb to soil particles and will not be
			Remarks: Float	s on water.
Othe	r adverse effects			
Prod	uct:			
	Additional ecological infor- mation		ozone creation Product is a mi	ozone depletion potential, photochemical potential or global warming potential. xture of non-volatile components, which will ne air in any significant quantities under normal se.
			Poorly soluble Causes physic	nixture. al fouling of aquatic organisms.
				s not cause chronic toxicity to aquatic organ- trations less than 1 mg/l.

Disposal methods

Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses.
	Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be dis- posed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

Version	Revision Date:	SDS Number:	Print Date: 02/18/2023		
2.1	02/17/2023	800010027938	Date of last issue: 08/12/2022		
		Pollution from Sł	nternational Convention for the Prevention of hips (MARPOL 73/78) which provides tech- controlling pollutions from ships.		
Contaminated packaging		to a recognized of the collector or c Disposal should	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.		
Local	legislation	•	be in accordance with applicable regional,		
Rema	rks		al laws and regulations.		

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
fumaric acid	110-17-8	5000	*
Ethanediol	107-21-1	5000	*
Ethylenediamine (SVHC)	107-15-3	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

Version	Revision Date:	SDS Number:	Print Date: 02/18/2023
2.1	02/17/2023	800010027938	Date of last issue: 08/12/2022

Calculated RQ exceeds reasonably attainable upper limit., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA., The components with RQs are given for information.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards		
SARA 313	:	The following components tablished by SARA Title III	<i>,</i>	rting levels es-
		Zinc dialkyl dithiophos- phate	84605-29-8	>= 1 - < 5 %
		Zinc dialkyldithiophos- phate	113706-15-3	>= 1 - < 5 %

Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

fumaric acid	110-17-8	0.1554 %
Ethylenediamine (SVHC)	107-15-3	0.003 %

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9
Zinc dialkyl dithiophosphate	84605-29-8
Zinc dialkyldithiophosphate	113706-15-3
fumaric acid	110-17-8
diphenylamine	122-39-4

California Prop. 65

WARNING: This product can expose you to chemicals including Ethanediol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9
Highly refined mineral oil	64742-70-7
Zinc dialkyl dithiophosphate	84605-29-8
Zinc dialkyldithiophosphate	113706-15-3

California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
--	------------

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

Version	Revision Date:	SDS Number:	Print Date: 02/18/2023
2.1	02/17/2023	800010027938	Date of last issue: 08/12/2022

Distillates (petroleum), hydrotreated light paraffinic 64742-55-8

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:							
REACH	:	Not established.					
TSCA	:	All components listed.					
DSL	:	All components listed.					

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

Full text of other abbreviations

ACGIH OSHA Z-1 ACGIH / TWA OSHA Z-1 / TWA Abbreviations and Acronyms	::	USA. ACGIH Threshold Limit Values (TLV) USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants 8-hour, time-weighted average 8-hour time weighted average The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
		ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level DSL = Canada Domestic Substance List EC = European Commission EC50 = Effective Concentration fifty ECETOC = European Center on Ecotoxicology and Toxicolo- gy Of Chemicals

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 2.1	Revision Date: 02/17/2023	SDS Number: 800010027938	Print Date: 02/18/2023 Date of last issue: 08/12/2022
		EINECS = The Chemical Subs EL50 = Effectiv ENCS = Japan Inventory EWC = Europe GHS = Globally Labelling of Chi IARC = Internat IATA = Internat IC50 = Inhibitor IL50 = Inhibitor IMDG = Internat INV = Chinese IP346 = Institut determination of KECI = Korea E LC50 = Lethal I LL/EL/IL = Leth LL50 = Lethal I US50 = Lethal I MARPOL = Internat NOEC/NOEL = served Effect L OE_HPV = Occ PBT = Persiste PICCS = Philip Substances PNEC = Predic REACH = Regi Chemicals RID = Regulatid gerous Goods I SKIN_DES = S STEL = Short to TRA = Targeted TSCA = US To TWA = Time-W	e Loading fifty ese Existing and New Chemical Substances an Waste Code y Harmonised System of Classification and emicals tional Agency for Research on Cancer ional Air Transport Association y Concentration fifty y Level fifty tional Maritime Dangerous Goods Chemicals Inventory te of Petroleum test method N° 346 for the of polycyclic aromatics DMSO-extractables Existing Chemicals Inventory Concentration fifty Dose fifty per cent. al Loading/Effective Loading/Inhibitory loading oading fifty ernational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob- evel cupational Exposure - High Production Volume nt, Bioaccumulative and Toxic pine Inventory of Chemicals and Chemical ted No Effect Concentration stration Evaluation And Authorisation Of
		-	endment from the previous version.
Sou	rces of key data used to	: The quoted dat	a are from, but not limited to, one or more

Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
Revision Date	:	02/17/2023

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T3 Fleet 15W-40

Version	Revision Date:	SDS Number:
2.1	02/17/2023	800010027938

Print Date: 02/18/2023 Date of last issue: 08/12/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN