According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 15W-40

Version 1.2	Revision Date: 02/17/2023	SDS Numb 800010033		Print Date: 02/18/2023 Date of last issue: 02/06/2023
SECTION	1. IDENTIFICATION			
Produ	ct name	: Shell R	otella T6 1	15W-40
Product code		: 001H0327		
Manu	facturer or supplier's	details		
Manu	facturer/Supplier	PO Bo	Dil Produc x 4427 on TX 772	
	Request mer Service		7-276-728	35

Emergency telephone number

Spill Information	:	877-242-7400
Health Information	:	877-504-9351

Recommended use of the chemical and restrictions on use

Recommended use : Engine oil.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Long-term (chronic) aquatic : Category 3 hazard

GHS label elements

Hazard pictograms	:	No symbol
Signal word	:	No signal word
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P273 Avoid release to the environment. Response: No precautionary phrases.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 15W-40

Version	Revision Date:
1.2	02/17/2023

SDS Number: 800010033090

Print Date: 02/18/2023 Date of last issue: 02/06/2023

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn. The classification of this material is based on OSHA HCS 2012 criteria.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Synthetic base oil and additives. Highly refined mineral oil. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. The highly refined mineral oil is only present as additive dilu- ent. Classification based on DMSO extract content < 3% (Regula- tion (EC) 1272/2008, Annex VI, Part 3, Note L).
		* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4, 64741-89-5.

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Alkyl borate		Trade secret	0.1 - 0.99
Dialkyl alkaryl ami- nomethyl dicarbox- ylate		Trade secret	0.1 - 0.99
Calcium sulphonate	Benzenesul- fonic acid, mono-C16-24- alkyl derivs., calcium salts	70024-69-0	0.1 - 0.99
Alkaryl amine	bis(nonylphenyl)amine	36878-20-3	1 - 3
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *		Not Assigned	0 - 90

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 15W-40

Version	Revision Date:	SDS Number:
1.2	02/17/2023	800010033090

Print Date: 02/18/2023 Date of last issue: 02/06/2023

CAS Number is withheld as a trade secret.

SECTION 4. FIRST-AID MEASUR	ES	
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Indication of any immediate medical attention and special treatment needed	:	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 15W-40

Version	Revision Date:	SDS Number:	Print Date: 02/18/2023
1.2	02/17/2023	800010033090	Date of last issue: 02/06/2023

relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions :	:	Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for : containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk as- sessment of local circumstances to help determine appropri- ate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Further information on stor- age stability	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 15W-40

Version 1.2	Revision Date: 02/17/2023	SDS Number: 800010033090	Print Date: 02/18/2023 Date of last issue: 02/06/2023
Pack	aging material		al: For containers or container linings, use mild ensity polyethylene. erial: PVC.
Conta	ainer Advice		ontainers should not be exposed to high tem- use of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-	-	
		late matter)		

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	:	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
		Where material is heated, spraved or mist formed, there is

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information: Define procedures for safe handling and maintenance of controls.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.2	Revision Date: 02/17/2023	SDS Number: 800010033090	Print Date: 02/18/2023 Date of last issue: 02/06/2023
		measures rele product. Ensure approp equipment use equipment, loc Drain down sy nance. Retain drain d subsequent re Always observ washing hands drinking, and/o protective equ taminated clot	rain workers in the hazards and control evant to normal activities associated with this priate selection, testing and maintenance of ed to control exposure, e.g. personal protective cal exhaust ventilation. Astem prior to equipment break-in or mainte- owns in sealed storage pending disposal or ecycle. We good personal hygiene measures, such as s after handling the material and before eating, for smoking. Routinely wash work clothing and ipment to remove contaminants. Discard con- hing and footwear that cannot be cleaned. housekeeping.
Perso	onal protective equip	oment	
	iratory protection	: No respiratory conditions of u In accordance tions should be If engineering tions to a level select respirat cific conditions Check with res Where air-filte priate combina Select a filter s	with good industrial hygiene practices, precau- e taken to avoid breathing of material. controls do not maintain airborne concentra- l which is adequate to protect worker health, ory protection equipment suitable for the spe- s of use and meeting relevant legislation. spiratory protective equipment suppliers. ring respirators are suitable, select an appro- ation of mask and filter. suitable for the combination of organic gases and particles [Type A/Type P boiling point
	protection emarks	gloves approv US: F739) ma suitable chemi gloves Suitabi usage, e.g. fre sistance of glo glove suppliers Personal hygie Gloves must o gloves, hands cation of a nor For continuous through time o 480 minutes w short-term/spla recognize that may not be av	ontact with the product may occur the use of ed to relevant standards (e.g. Europe: EN374, de from the following materials may provide ical protection. PVC, neoprene or nitrile rubber lity and durability of a glove is dependent on equency and duration of contact, chemical re- ove material, dexterity. Always seek advice from s. Contaminated gloves should be replaced. ene is a key element of effective hand care. only be worn on clean hands. After using should be washed and dried thoroughly. Appli- n-perfumed moisturizer is recommended. s contact we recommend gloves with break- of more than 240 minutes with preference for > where suitable gloves can be identified. For ash protection we recommend the same but is suitable gloves offering this level of protection valable and in this case a lower breakthrough cceptable so long as appropriate maintenance

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.2	Revision Date: 02/17/2023	SDS Number: 800010033090	Print Date: 02/18/2023 Date of last issue: 02/06/2023		
		a good predic dependent or Glove thickne	tent regimes are followed. Glove thickness is not otor of glove resistance to a chemical as it is the exact composition of the glove material. the should be typically greater than 0.35 mm the glove make and model.		
Еуе р	protection		nandled such that it could be splashed into eyes, ewear is recommended.		
Skin	and body protection	work clothes.	Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.		
Prote	ective measures		Personal protective equipment (PPE) should meet recom- mended national standards. Check with PPE suppliers.		
Ther	mal hazards	: Not applicable	e		
Envi	ronmental exposure o	controls			
Gene	eral advice	vant environn of the environ necessary, pr charged to wa municipal or i discharge to s Local guidelir	iate measures to fulfill the requirements of rele- nental protection legislation. Avoid contamination ment by following advice given in Section 6. If revent undissolved material from being dis- aste water. Waste water should be treated in a ndustrial waste water treatment plant before surface water. hes on emission limits for volatile substances erved for the discharge of exhaust air containing		
SECTION	9. PHYSICAL AND C	HEMICAL PROPER	TIES		
Appe	arance	: liquid			
Color	ur	: Clear amber			
Oda		. Clight budge	horh on		

- Odour : Slight hydrocarbon
- Odour Threshold : Data not available
- pH : Not applicable pour point : -39 °C / -38 °F Method: ASTM D97
- Initial boiling point and boiling
range:> 280 °C / 536 °F
estimated value(s)Flash point:249 °C / 480 °F
Method: ASTM D92 (COC)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Versi 1.2	on Revision Date: 02/17/2023		S Number: 0010033090	Print Date: 02/18/2023 Date of last issue: 02/06/2023
I	Flammability Flammability (solid, gas)		Not applicable	
	Flammability (liquids)	:	Not classified as	flammable but will burn.
I	Lower explosion limit and upp Upper explosion limit / up- per flammability limit			nmability limit
	Lower explosion limit / Lower flammability limit	:	Typical 1 %(V)	
v	√apour pressure	:	< 0.5 Pa (20 °C /	68 °F)
			estimated value(5)
I	Relative vapour density	:	> 1 estimated value(s	s)
I	Relative density	:	0.855 (15.0 °C /	59.0 °F)
I	Density	:	855 kg/m3 (15.0 Method: ASTM D	
;	Solubility(ies) Water solubility	:	negligible	
	Solubility in other solvents	:	Data not availabl	e
	Partition coefficient: n- octanol/water	:	log Pow: > 6 (based on inform	ation on similar products)
,	Auto-ignition temperature	:	> 320 °C / 608 °F	-
I	Decomposition temperature	:	Data not availabl	e
v	Viscosity Viscosity, dynamic	:	Data not availabl	e
	Viscosity, kinematic	:	14.7 mm2/s (100	°C / 212 °F)
			Method: ASTM D	
			130.8 mm2/s (40	.0 °C / 104.0 °F)
			Method: ASTM D	0445
I	Explosive properties	:	Classification Co	de: Not classified
(Oxidizing properties	:	Data not availabl	e
(Conductivity	:	This material is n	ot expected to be a static accumulator.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 15W-40

Version	Revision Date:	SDS Number:	Print Date: 02/18/2023
1.2	02/17/2023	800010033090	Date of last issue: 02/06/2023

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	 Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).
----------------------	--

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:		
Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 15W-40

Version	Revision Date:	SDS Number:	F
1.2	02/17/2023	800010033090	Ľ

Print Date: 02/18/2023 Date of last issue: 02/06/2023

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

Alkyl borate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Dialkyl alkaryl aminomethyl dicarboxylate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Calcium sulphonate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
ΝΤΡ	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 15W-40

Version	Revision Date:	SDS Number:	Print Date: 02/18/2023
1.2	02/17/2023	800010033090	Date of last issue: 02/06/2023

Reproductive toxicity

Product:

Effects on fertility

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

1

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).
Ecotoxicity	
Product: Toxicity to fish (Acute toxici- :	

ty)

Remarks: LL/EL/IL50 10-100 mg/I

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

	Revision Date: 02/17/2023		0S Number: 0010033090	Print Date: 02/18/2023 Date of last issue: 02/06/2023
			Harmful	
	y to daphnia and other invertebrates (Acute)	:	Remarks: LL/EL/ Harmful	/IL50 10-100 mg/l
Toxicity icity)	/ to algae (Acute tox-	:	Remarks: LL/EL/ Harmful	/IL50 10-100 mg/l
Toxicity icity)	y to fish (Chronic tox-	:	Remarks: NOEC	:/NOEL > 10 - <=100 mg/l
	y to daphnia and other invertebrates (Chron- ity)	:	Remarks: NOEC	C/NOEL > 10 - <=100 mg/l
	y to microorganisms toxicity)	:	Remarks: NOEC	2/NOEL > 10 - <=100 mg/l
Compo	onents:			
	or (Acute aquatic tox-	:	1	
icity)		itv		
icity)	tence and degradabil	ity		
icity) Persist <u>Produc</u>	tence and degradabil	ity :	Major constituen	adily biodegradable. ts are inherently biodegradable, but contair may persist in the environment.
icity) Persist <u>Produc</u> Biodeg	tence and degradabil	ity :	Major constituen	ts are inherently biodegradable, but contain
icity) Persist Product Biodeg Bioacc Product	tence and degradabil <u>ct:</u> radability cumulative potential	:	Major constituen components that	ts are inherently biodegradable, but contair
icity) Persist Produc Biodeg Bioacco Produc Bioacco	tence and degradabil <u>ot:</u> radability cumulative potential ot:	:	Major constituen components that Remarks: Conta	ts are inherently biodegradable, but contain may persist in the environment.
icity) Persist Produc Biodeg Bioacco Produc Bioacco	tence and degradabil <u>ct:</u> radability cumulative potential <u>ct:</u> umulation cy in soil <u>ct:</u>	:	Major constituen components that Remarks: Conta cumulate. Remarks: Liquid	ts are inherently biodegradable, but contair may persist in the environment.
icity) Persist Produc Biodeg Bioacce Bioacce Mobilit Produc	tence and degradabil <u>ct:</u> radability cumulative potential <u>ct:</u> umulation cy in soil <u>ct:</u>	:	Major constituen components that Remarks: Conta cumulate. Remarks: Liquid	ts are inherently biodegradable, but contain may persist in the environment. ins components with the potential to bioac- under most environmental conditions. ind has low mobility
icity) Persist Produc Biodeg Bioacce Bioacce Mobilit Produc Mobility	tence and degradabil <u>ct:</u> radability cumulative potential <u>ct:</u> umulation cy in soil <u>ct:</u>	:	Major constituen components that Remarks: Conta cumulate. Remarks: Liquid Adsorbs to soil a	ts are inherently biodegradable, but contain may persist in the environment. ins components with the potential to bioac- under most environmental conditions. ind has low mobility
icity) Persist Produc Biodeg Bioacce Bioacce Mobilit Produc Mobility	tence and degradabil <u>ct:</u> radability cumulative potential <u>ct:</u> umulation cy in soil <u>ct:</u> / adverse effects	:	Major constituen components that Remarks: Conta cumulate. Remarks: Liquid Adsorbs to soil a	ts are inherently biodegradable, but contain may persist in the environment. ins components with the potential to bioac- under most environmental conditions. ind has low mobility

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 15W-40

Version	Revision Date:	SDS Number:	Print Date: 02/18/2023
1.2	02/17/2023	800010033090	Date of last issue: 02/06/2023
Addition	onal ecological infor-	ozone creation Product is a mi be released to conditions of us Poorly soluble	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues :	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth- ods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste. Waste arising from a spillage or tank cleaning should be dis- posed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.
	MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tech- nical aspects at controlling pollutions from ships.
Contaminated packaging :	Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks	: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 15W-40

Version	Revision Date:	SDS Number:
1.2	02/17/2023	800010033090

Print Date: 02/18/2023 Date of last issue: 02/06/2023

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
2-methylpropan-1-ol	78-83-1	100	100 (F005)
Toluene	108-88-3	100	100 (F005)
Benzene	71-43-2	10	10 (D018)
Ethylbenzene	100-41-4	100	100 (F003)
Ethylbenzene	100-41-4	100	100 (F003)
Benzene	71-43-2	10	*

*: Calculated RQ exceeds reasonably attainable upper limit., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA., The components with RQs are given for information.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Toluene	108-88-3	0.0002 %
---------	----------	----------

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 15W-40

Version	Revision Date:	SDS Number:	Print Date: 02/18/2023
1.2	02/17/2023	800010033090	Date of last issue: 02/06/2023
	Benzene	71-43-2	0.0002 %
	Ethylbenzene	100-41-4	0.0002 %
	Naphthalene	91-20-3	0.0002 %

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-	72623-86-0
based	
Zinc dialkyl dithiophosphate	84605-29-8

California Prop. 65

WARNING: This product can expose you to chemicals including Benzene, Ethylbenzene, Naphthalene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-	72623-86-0
based	

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.
DSL	:	All components listed.

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-
		its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.2	Revision Date: 02/17/2023	SDS Number: 800010033090	Print Date: 02/18/2023 Date of last issue: 02/06/2023
Abbreviations and Acronyms		ment can be lo	abbreviations and acronyms used in this docu- boked up in reference literature (e.g. scientific nd/or websites.
		Hygienists ADR = Europe Carriage of Da AICS = Austra ASTM = Amer BEL = Biologia BTEX = Benz CAS = Chemia CEFIC = Euro CLP = Classifi COC = Clevel DIN = Deutsch DMEL = Deriv DNEL = Deriv DNEL = Deriv DSL = Canada EC = Europea EC50 = Effect ECETOC = Europea EC50 = Effect ECHA = Europ EINECS = The Chemical Sub EL50 = Effect ENCS = Japa Inventory EWC = Europ GHS = Global Labelling of C IARC = Interna IC50 = Inhibito IMDG = Interna IC50 = Inhibito IMDG = Interna IC50 = Lethal LD50 = Lethal LD50 = Lethal LD50 = Lethal MARPOL = In Pollution From NOEC/NOEL served Effect OE_HPV = Oc PBT = Persist PICCS = Phili Substances	bean Chemicals Agency e European Inventory of Existing Commercial stances ve Loading fifty nese Existing and New Chemical Substances ean Waste Code ly Harmonised System of Classification and hemicals ational Agency for Research on Cancer ational Air Transport Association bry Concentration fifty ry Level fifty ational Maritime Dangerous Goods e Chemicals Inventory ute of Petroleum test method N° 346 for the of polycyclic aromatics DMSO-extractables Existing Chemicals Inventory Concentration fifty Dose fifty per cent. hal Loading/Effective Loading/Inhibitory loading Loading fifty ternational Convention for the Prevention of a Ships = No Observed Effect Concentration / No Ob-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Rotella T6 15W-40

Version	Revision Date:	SDS Number:	Print Date: 02/18/2023
1.2	02/17/2023	800010033090	Date of last issue: 02/06/2023
		Chemicals RID = Regulation gerous Goods & SKIN_DES = S STEL = Short te TRA = Targeted TSCA = US Too TWA = Time-W	stration Evaluation And Authorisation Of ons Relating to International Carriage of Dan- by Rail kin Designation erm exposure limit d Risk Assessment xic Substances Control Act deginted Average ersistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
Revision Date	:	02/17/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US/EN