According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Version 1.6	Revision Date: 03/01/2023		DS Number: 00001007199	Print Date: 03/02/2023 Date of last issue: 04/30/2018
SECTION	1. IDENTIFICATION			
Produ	ct name	:	Shell Omala S4 0	GX 150
Produ	ct code	:	001D7850	
Manu	facturer or supplier's	deta	ails	
	facturer/Supplier		Shell Oil Product PO Box 4427 Houston TX, 772	

	PO Box 4427
	Houston TX 77210-4427
	USA
SDS Request	: (+1) 877-276-7285
Customer Service	:

#### Emergency telephone number

Spill Information	:	877-242-7400
Health Information	:	877-504-9351

### Recommended use of the chemical and restrictions on use

Recommended use : Gear oil

### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements		
Hazard pictograms	No Hazard Symbol required	
Signal word	No signal word	
Hazard statements	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.	eria.
Precautionary statements	Prevention: No precautionary phrases. Response: No precautionary phrases. Storage: No precautionary phrases.	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Version	Revision Date:
1.6	03/01/2023

SDS Number: 800001007199

Print Date: 03/02/2023 Date of last issue: 04/30/2018

### Disposal:

No precautionary phrases.

### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Blend of polyolefins and additives.

### Hazardous components

Contains no hazardous ingredients according to GHS

#### **SECTION 4. FIRST-AID MEASURES** In case of skin contact Remove contaminated clothing. Flush exposed area with wa-• ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. Flush eye with copious quantities of water. In case of eye contact 1 Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention. If swallowed In general no treatment is necessary unless large quantities are swallowed, however, get medical advice. Most important symptoms : Oil acne/folliculitis signs and symptoms may include formation and effects, both acute and of black pustules and spots on the skin of exposed areas. delayed Ingestion may result in nausea, vomiting and/or diarrhoea. Protection of first-aiders When administering first aid, ensure that you are wearing the 5 appropriate personal protective equipment according to the incident, injury and surroundings. Indication of any immediate Treat symptomatically. medical attention and special treatment needed

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Version	Revision Date:	SDS Number:	Print Date: 03/02/2023
1.6	03/01/2023	800001007199	Date of last issue: 04/30/2018

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

### SECTION 7. HANDLING AND STORAGE

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Vers 1.6	ion Revision Date: 03/01/2023		9S Number: 0001007199	Print Date: 03/02/2023 Date of last issue: 04/30/2018
	Technical measures	:	vapours, mists or Use the informatic sessment of local	ventilation if there is risk of inhalation of aerosols. on in this data sheet as input to a risk as- circumstances to help determine appropri- fe handling, storage and disposal of this
Advice on safe handling		:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.	
	Avoidance of contact	:	Strong oxidising a	gents.
	Product Transfer	:		and bonding procedures should be used nsfer operations to avoid static accumulation.
	Further information on stor- age stability	:	place.	htly closed and in a cool, well-ventilated led and closable containers.
			Store at ambient t	emperature.
	Packaging material	:	Suitable material: steel or high dens Unsuitable materia	
	Container Advice	:		ainers should not be exposed to high tem- e of possible risk of distortion.

### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

### **Biological occupational exposure limits**

No biological limit allocated.

### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substanc-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Version	Revision Date:	SDS Number:	Print Date: 03/02/2023
1.6	03/01/2023	800001007199	Date of last issue: 04/30/2018

es http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures :	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	<ul> <li>General Information:</li> <li>Define procedures for safe handling and maintenance of controls.</li> <li>Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.</li> <li>Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.</li> <li>Drain down system prior to equipment break-in or maintenance.</li> <li>Retain drain downs in sealed storage pending disposal or subsequent recycle.</li> <li>Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.</li> <li>Practice good housekeeping.</li> </ul>
Personal protective equipmen	t

Respiratory protection	:	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].
Hand protection Remarks	:	Where hand contact with the product may occur the use of

# Remarks

Where hand contact with the product may occur the use of

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Version 1.6	Revision Date: 03/01/2023		0S Number: 0001007199	Print Date: 03/02/2023 Date of last issue: 04/30/2018
			US: F739) made is suitable chemical gloves Suitability usage, e.g. freque sistance of glove glove suppliers. O Personal hygiene Gloves must only gloves, hands sho cation of a non-per For continuous co through time of m 480 minutes when short-term/splash recognize that sui may not be availat time maybe accept and replacement a good predictor of dependent on the Glove thickness s	to relevant standards (e.g. Europe: EN374, from the following materials may provide protection. PVC, neoprene or nitrile rubber and durability of a glove is dependent on ency and duration of contact, chemical re- material, dexterity. Always seek advice from Contaminated gloves should be replaced. is a key element of effective hand care. be worn on clean hands. After using build be washed and dried thoroughly. Appli- erfumed moisturizer is recommended. ontact we recommend gloves with break- ore than 240 minutes with preference for > re suitable gloves can be identified. For protection we recommend the same but itable gloves offering this level of protection ble and in this case a lower breakthrough otable so long as appropriate maintenance regimes are followed. Glove thickness is not of glove resistance to a chemical as it is exact composition of the glove material. should be typically greater than 0.35 mm glove make and model.
Eye	e protection	:		lled such that it could be splashed into eyes, ar is recommended.
Ski	n and body protection	:	work clothes.	not ordinarily required beyond standard to wear chemical resistant gloves.
Pro	tective measures	:		ve equipment (PPE) should meet recom- standards. Check with PPE suppliers.
The	ermal hazards	:	Not applicable	
Env	vironmental exposure co	ontro	bls	
Gei	neral advice	:	vant environment of the environmer	measures to fulfill the requirements of rele- al protection legislation. Avoid contamination at by following advice given in Section 6. If nt undissolved material from being dis-

charged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:Liquid at room temperature.Colour:amber

vapour.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Vers 1.6	sion	Revision Date: 03/01/2023		S Number: 0001007199	Print Date: 03/02/2023 Date of last issue: 04/30/2018
	Odour		:	Data not availabl	e
	Odour <sup>-</sup>	Threshold	:	Data not availabl	e
	рН		:	Not applicable	
	pour po	bint	:	-45 °C / -49 °F Method: ISO 301	6
	Melting	/ freezing point		Data not availabl	e
	Initial b range	oiling point and boiling	:	> 280 °C / 536 °F estimated value(	
	Flash p	oint	:	238 °C / 460 °F	
				Method: ISO 259	2
	Evapor	ation rate	:	Data not availabl	e
	Flamm: Flan	ability nmability (solid, gas)	:	Not applicable	
	Flan	nmability (liquids)	:	Not classified as	flammable but will burn.
	Upp	explosion limit and upp er explosion limit / up- flammability limit		xplosion limit / flan Typical 10 %(V)	nmability limit
		er explosion limit / er flammability limit	:	Typical 1 %(V)	
	Vapour	pressure	:	< 0.5 Pa (20 °C /	68 °F)
				estimated value(	5)
	Relative	e vapour density	:	> 5	
	Relative	e density	:	0.877 (15 °C / 59	°F)
	Density	,	:	877 kg/m3 (15.0 Method: ISO 121	
	Solubili Wat	ty(ies) er solubility	:	negligible	
	Solu	ubility in other solvents	:	Data not availabl	e
	Partition octanol	n coefficient: n- /water	:	log Pow: > 6 (based on inform	ation on similar products)
	Auto-ig	nition temperature	:	> 320 °C / 608 °F	-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

ersion .6	Revision Date: 03/01/2023		S Number: 0001007199	Print Date: 03/02/2023 Date of last issue: 04/30/2018
Decor	mposition temperature	:	Data not availab	le
Visco: Vis	sity scosity, dynamic	:	Data not availab	le
Vis	scosity, kinematic	:	157.7 mm2/s (40	0.0 °C / 104.0 °F)
			Method: Unspec	ified
			21.7 mm2/s (100	) °C / 212 °F)
			Method: Unspec	ified
Explo	sive properties	:	Classification Co	ode: Not classified
Oxidiz	zing properties	:	Data not availab	le
Cond	uctivity	:	This material is r	not expected to be a static accumulator.
Partic	le size	:	Data not availab	le

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

### SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and
		the toxicology of similar products. Unless indicated otherwise,
		the data presented is representative of the product as a
		whole, rather than for individual component(s).

### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

### Acute toxicity

### Product:

Acute oral toxicity

: LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Version 1.6	Revision Date: 03/01/2023	SDS Number: 800001007199	Print Date: 03/02/2023 Date of last issue: 04/30/2018
		Based on availa	ble data, the classification criteria are not met.
Acute inhalation toxicity		: Remarks: Based on available data, the classification criteria are not met.	
Acute dermal toxicity		: LD50 (Rabbit): Remarks: Low t Based on availa	

### Skin corrosion/irritation

### Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

### Serious eye damage/eye irritation

### Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

### Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

### Product:

Genotoxicity in vivo : Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

### Carcinogenicity

### Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Version	Revision Date:	SDS Number:
1.6	03/01/2023	800001007199

Print Date: 03/02/2023 Date of last issue: 04/30/2018

### **Reproductive toxicity**

### Product:

Effects on fertility

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

### STOT - single exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

#### STOT - repeated exposure

### Product:

Remarks: Based on available data, the classification criteria are not met.

### Aspiration toxicity

### Product:

Not an aspiration hazard.

#### Further information

### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

### **SECTION 12. ECOLOGICAL INFORMATION**

Basis for assessment	: Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).
Fcotoxicity	

### Ecotoxicity

### Product:

Toxicity to fish (Acute toxici- :

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Vers 1.6	sion	Revision Date: 03/01/2023		9S Number: 0001007199	Print Date: 03/02/2023 Date of last issue: 04/30/2018
	ty)			Remarks: Based of are not met. Practically non tox LL/EL/IL50 > 100	
		v to daphnia and other invertebrates (Acute	:	Remarks: Based of are not met. Practically non tox LL/EL/IL50 > 100	
	Toxicity icity)	v to algae (Acute tox-	:	Remarks: Based of are not met. Practically non tox LL/EL/IL50 > 100	
	Toxicity icity)	v to fish (Chronic tox-	:	Remarks: Based of are not met.	on available data, the classification criteria
		v to daphnia and other invertebrates (Chron- ty)	:	Remarks: Based of are not met.	on available data, the classification criteria
		<pre>v to microorganisms toxicity)</pre>	:	Remarks: Based of are not met.	on available data, the classification criteria
	Persistence and degradabil		ty		
	Produc				
	Biodegi	radability	:	Major constituents components that in Persistent per IMC International Oil P tion: "A non-persis consists of hydroc by volume, distills at least 95% of wh	ollution Compensation (IOPC) Fund defini- stent oil is oil, which, at the time of shipment, carbon fractions, (a) at least 50% of which, at a temperature of 340°C (645°F) and (b) nich, by volume, distils at a temperature of en tested by the ASTM Method D-86/78 or
	Bioacc	umulative potential			
	Produc Bioaccu	<u>:t:</u> umulation	:	Remarks: Contain cumulate.	is components with the potential to bioac-
	Mobilit	y in soil			
	Product Mobility		:		under most environmental conditions. vill adsorb to soil particles and will not be

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

ersion .6	Revision Date: 03/01/2023	SDS Number: 800001007199	Print Date: 03/02/2023 Date of last issue: 04/30/2018
		mobile.	
		Remarks: Float	s on water.
Othe	r adverse effects		
Prod	uct:		
Additi matio	ional ecological infor- n	ozone creation Product is a mi	ozone depletion potential, photochemical potential or global warming potential. xture of non-volatile components, which will no air in any significant quantities under normal se.
		Poorly soluble Causes physica	mixture. al fouling of aquatic organisms.
	13. DISPOSAL CONS		
Wast	e from residues	toxicity and phy determine the p ods in compliar Waste product ground water, o Do not dispose courses. Do not dispose drain into the g contamination. Waste arising f posed of in acc to a recognised	ycle if possible. sibility of the waste generator to determine the vsical properties of the material generated to proper waste classification and disposal meth- nee with applicable regulations. should not be allowed to contaminate soil or or be disposed of into the environment. into the environment, in drains or in water of tank water bottoms by allowing them to round. This will result in soil and groundwater rom a spillage or tank cleaning should be dis- pordance with prevailing regulations, preferably d collector or contractor. The competence of the tractor should be established beforehand.
		Pollution from S	International Convention for the Prevention of Ships (MARPOL 73/78) which provides tech- t controlling pollutions from ships.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

# Remarks : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Version	Revision Date:	SDS Number:
1.6	03/01/2023	800001007199

Print Date: 03/02/2023 Date of last issue: 04/30/2018

#### **SECTION 14. TRANSPORT INFORMATION**

#### **National Regulations**

#### US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

#### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

### IMDG-Code

Not regulated as a dangerous good

#### Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

#### Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

### SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know Act

\*: This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### **Clean Water Act**

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

#### US State Regulations

#### Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy paraffinic

64742-54-7

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Version	Revision Date:	SDS Number:	Print Date: 03/02/2023
1.6	03/01/2023	800001007199	Date of last issue: 04/30/2018

Distillates (petroleum), hydrotreated light

64742-47-8

#### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

#### The components of this product are reported in the following inventories:

TSCA	: All components listed	•
DSL	: All components listed	

### **SECTION 16. OTHER INFORMATION**

#### Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

### Full text of other abbreviations

Abbreviations and Acronyms	:	The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
		ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level DSL = Canada Domestic Substance List EC = European Commission EC50 = Effective Concentration fifty ECETOC = European Chemicals Agency EINECS = The European Inventory of Existing Commercial
		Chemical Substances

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# Shell Omala S4 GX 150

Version 1.6	Revision Date: 03/01/2023	SDS Number: 800001007199	Print Date: 03/02/2023 Date of last issue: 04/30/2018
		EL50 = Effecti	ve Loading fifty
		ENCS = Japar Inventory	nese Existing and New Chemical Substances
			ean Waste Code
			y Harmonised System of Classification and
			ational Agency for Research on Cancer
			tional Air Transport Association
			ory Concentration fifty
		IL50 = Inhibito	
			ational Maritime Dangerous Goods
			Chemicals Inventory
			ute of Petroleum test method N° 346 for the of polycyclic aromatics DMSO-extractables
			Existing Chemicals Inventory
			Concentration fifty
			Dose fifty per cent.
			hal Loading/Effective Loading/Inhibitory loading
		MARPOL = Int	ternational Convention for the Prevention of
			= No Observed Effect Concentration / No Ob-
		served Effect I	
			cupational Exposure - High Production Volume ent, Bioaccumulative and Toxic
			opine Inventory of Chemicals and Chemical
		Substances	spine inventory of chemicals and chemical
			cted No Effect Concentration
		REACH = Reg	istration Evaluation And Authorisation Of
		Chemicals	
		5	ions Relating to International Carriage of Dan-
		gerous Goods	Bkin Designation
			term exposure limit
			ed Risk Assessment
			oxic Substances Control Act
		TWA = Time-V	Veighted Average
		vPvB = very P	ersistent and very Bioaccumulative
A ver	tical bar (I) in the left	margin indicates an an	nendment from the previous version.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
Revision Date	:	03/01/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200 Shell Omala S4 GX 150

# Shell Olliala 34 GA 150

Version	Revision Date:	SDS Number:	F
1.6	03/01/2023	800001007199	C

Print Date: 03/02/2023 Date of last issue: 04/30/2018

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US/EN