According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Version 1.2	Revision Date: 02/17/2023	SDS Number: 800010035729	Print Date: 04/29/2023 Date of last issue: 01/05/2022
SECTION	1. IDENTIFICATION		
Produ	uct name	: Shell Tellus S4	VK 46
Produ	uct code	: 001H5432	
Manu	facturer or supplier's	details	
Manu	facturer/Supplier	: Shell Oil Prod PO Box 4427 Houston TX 7 USA	
	Request omer Service	: (+1) 877-276-7 :	285
	gency telephone nur	nber	
		: 877-242-7400 : 877-504-9351	
Healt	h Information	: 877-504-9351	tions on use

Recommended use of the chemical and restrictions on use

Recommended use : Hydraulic oil

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements Hazard pictograms	:	No Hazard Symbol required
Signal word	:	No signal word
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	:	Prevention: No precautionary phrases. Response: No precautionary phrases. Storage: No precautionary phrases.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Version Revision Date: 1.2 02/17/2023

SDS Number: 800010035729

Print Date: 04/29/2023 Date of last issue: 01/05/2022

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis. Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Blend of polyolefins and additives.

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Distillates (Fischer - Tropsch), heavy, C18-50 – branched, cyclic and linear	Distillates (Fischer- Tropsch), heavy, C18-50- branched, cy- clic and linear	848301-69-9	65 - 70
Lubricating oils (pe- troleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	Lubricating oils (petroleum), C15-30, hy- drotreated neutral oil- based	72623-86-0	1-5
Distillates (Fischer - Tropsch), heavy, C18-50 – branched, cyclic and linear	Distillates (Fischer- Tropsch), heavy, C18-50- branched, cy- clic and linear	848301-69-9	1 - 5
Triazole derivative	1-(N,N-bis(2- ethylhex- yl)aminomethyl)-1,2,4-triazole	91273-04-0	0.01 - 0.024

SECTION 4. FIRST-AID MEASURES

In case of skin contact

Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Vers 1.2	sion	Revision Date: 02/17/2023		0S Number: 0010035729	Print Date: 04/29/2023 Date of last issue: 01/05/2022
				under the skin car casualty should be for symptoms to d	pressure equipment, injection of product n occur. If high pressure injuries occur, the e sent immediately to a hospital. Do not wait levelop. tention even in the absence of apparent
	In case	of eye contact	:	Remove contact le rinsing.	pious quantities of water. enses, if present and easy to do. Continue on occurs, obtain medical attention.
	lf swalle	owed	:		tment is necessary unless large quantities owever, get medical advice.
		portant symptoms ects, both acute and l	:	of black pustules a Ingestion may res Local necrosis is a	s signs and symptoms may include formation and spots on the skin of exposed areas. Fult in nausea, vomiting and/or diarrhoea. Evidenced by delayed onset of pain and Few hours following injection.
	Protect	ion of first-aiders	:		ng first aid, ensure that you are wearing the nal protective equipment according to the d surroundings.
	medica	on of any immediate I attention and special ent needed	:	Treat symptomation	cally.
				vention and possi age and loss of fu Because entry wo ousness of the un determine the external anaesthetics or he can contribute to a surgical decompre- eign material shou	ection injuries require prompt surgical inter- bly steroid therapy, to minimise tissue dam- inction. bunds are small and do not reflect the seri- derlying damage, surgical exploration to ent of involvement may be necessary. Local of soaks should be avoided because they swelling, vasospasm and ischaemia. Prompt ession, debridement and evacuation of for- uld be performed under general anaesthet- loration is essential.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke).

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Vers 1.2	sion	Revision Date: 02/17/2023		S Number: 0010035729	Print Date: 04/29/2023 Date of last issue: 01/05/2022
				occurs.	may be evolved if incomplete combustion ic and inorganic compounds.
Specific extinguishing meth- ods		:		measures that are appropriate to local cir- he surrounding environment.	
	Special protective equipment for firefighters		:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).	

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Avoid contact with skin and eyes.
Environmental precautions :	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
	Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for : containment and cleaning up	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice :	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of

SECTION 7. HANDLING AND STORAGE

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be

this Safety Data Sheet.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Version 1.2	Revision Date: 02/17/2023		DS Number: 00010035729	Print Date: 04/29/2023 Date of last issue: 01/05/2022		
				handling equipment should be used. of any contaminated rags or cleaning mate- revent fires.		
Avoidance of contact		:	Strong oxidising agents.			
Further information on stor- age stability		:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.			
			Store at ambient	temperature.		
Pac	Packaging material		Suitable material: For containers or container linings, use mil steel or high density polyethylene. Unsuitable material: PVC.			
Con	tainer Advice	:		tainers should not be exposed to high tem- e of possible risk of distortion.		

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.	Engineering measures	:	
--	----------------------	---	--

Where material is heated, sprayed or mist formed, there is

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.2	Revision Date: 02/17/2023	SDS Number: 800010035729	Print Date: 04/29/2023 Date of last issue: 01/05/2022
		greater potential	for airborne concentrations to be generated.
		controls. Educate and trai measures releva product. Ensure appropria equipment used equipment, local Drain down syste nance. Retain drain dow subsequent recy Always observe washing hands a drinking, and/or	es for safe handling and maintenance of in workers in the hazards and control ant to normal activities associated with this ate selection, testing and maintenance of to control exposure, e.g. personal protective exhaust ventilation. em prior to equipment break-in or mainte- vns in sealed storage pending disposal or
		Practice good ho	
	nal protective equipn ratory protection	: No respiratory pro- conditions of use In accordance we tions should be to If engineering con- tions to a level we select respiratory cific conditions of Check with respin Where air-filtering priate combinations	rotection is ordinarily required under normal e. hith good industrial hygiene practices, precau- aken to avoid breathing of material. ontrols do not maintain airborne concentra- which is adequate to protect worker health, y protection equipment suitable for the spe- of use and meeting relevant legislation. iratory protective equipment suppliers. In grespirators are suitable, select an appro- tion of mask and filter. itable for the combination of organic gases d particles [Type A/Type P boiling point
	protection marks	gloves approved US: F739) made suitable chemica gloves Suitability usage, e.g. frequ sistance of glove glove suppliers. Personal hygien Gloves must onl gloves, hands sh cation of a non-p For continuous of	tact with the product may occur the use of to relevant standards (e.g. Europe: EN374, e from the following materials may provide al protection. PVC, neoprene or nitrile rubber y and durability of a glove is dependent on uency and duration of contact, chemical re- e material, dexterity. Always seek advice from Contaminated gloves should be replaced. e is a key element of effective hand care. y be worn on clean hands. After using nould be washed and dried thoroughly. Appli- perfumed moisturizer is recommended. contact we recommend gloves with break- more than 240 minutes with preference for >

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Version 1.2	Revision Date: 02/17/2023		DS Number: 0010035729	Print Date: 04/29/2023 Date of last issue: 01/05/2022
			short-term/splash recognize that suit may not be availal time maybe accept and replacement r a good predictor of dependent on the Glove thickness st	e suitable gloves can be identified. For protection we recommend the same but table gloves offering this level of protection ble and in this case a lower breakthrough otable so long as appropriate maintenance regimes are followed. Glove thickness is not of glove resistance to a chemical as it is exact composition of the glove material. hould be typically greater than 0.35 mm glove make and model.
Eye pr	rotection	:		led such that it could be splashed into eyes, Ir is recommended.
Skin and body protection		:	Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.	
Protec	tive measures	:		e equipment (PPE) should meet recom- standards. Check with PPE suppliers.
Therm	al hazards	:	Not applicable	

Environmental exposure controls

General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	colourless
Odour	:	Data not available
Odour Threshold	:	Data not available
рН	:	Not applicable
Melting / freezing point	:	Data not available
pour point		-51 °C / -60 °F Method: ASTM D97
Initial boiling point and boiling	:	> 280 °C / 536 °F

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.2	Revision Date: 02/17/2023		S Number: 0010035729	Print Date: 04/29/2023 Date of last issue: 01/05/2022
range)		estimated value	(s)
Flash	point	:	260 °C / 500 °F	
			Method: ISO 25	92
Evap	oration rate	:	Data not availat	ble
	mability ammability (solid, gas)	:	Not applicable	
FI	ammability (liquids)	:	Not classified as	s flammable but will burn.
U	er explosion limit and upp oper explosion limit / up- er flammability limit			
	ower explosion limit / ower flammability limit	:	Typical 1 %(V)	
Vapo	ur pressure	:	< 0.5 Pa (20 °C	/ 68 °F)
			estimated value	(S)
Relat	ive vapour density	:	> 5	
Dens	ity	:	841 kg/m3 (15.0 Method: DIN EN	
	pility(ies) ater solubility	:	negligible	
So	olubility in other solvents	:	Data not availat	ble
	ion coefficient: n- ol/water	:	log Pow: > 6 (based on inforr	nation on similar products)
Auto-	ignition temperature	:	> 320 °C / 608 °	'F
Deco	mposition temperature	:	Data not availat	ble
Visco Vi	sity scosity, dynamic	:	Data not availat	ble
Vi	scosity, kinematic	:	46 mm2/s (40.0	°C / 104.0 °F)
			Method: ASTM	D445
			10.4 mm2/s (10	0 °C / 212 °F)
			Method: ASTM	D445
Explo	osive properties	:	Classification C	ode: Not classified

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Ve 1.	ersion 2	Revision Date: 02/17/2023		S Number: 0010035729	Print Date: 04/29/2023 Date of last issue: 01/05/2022
	Oxidizi	ng properties	:	Data not availabl	e
	Condu	ctivity	:	This material is n	ot expected to be a static accumulator.
S	ECTION 1	0. STABILITY AND RE	EAC	ΤΙVΙΤΥ	
	Reactiv	<i>r</i> ity	:		s not pose any further reactivity hazards in listed in the following sub-paragraph.
	Chemio	cal stability	:	Stable.	
	Possibi tions	ility of hazardous reac-	:	Reacts with stror	ng oxidising agents.
				-	

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:		
Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Version	Revision Date:	SDS Number:	Print Date: 04/29/2023
1.2	02/17/2023	800010035729	Date of last issue: 01/05/2022

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

Triazole derivative:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Reproductive toxicity	
Product:	
Effects on fertility	: Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Version	Revision Date:	SDS Number:	Print Date: 04/29/2023
1.2	02/17/2023	800010035729	Date of last issue: 01/05/2022

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment :	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxici- : ty)	Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to daphnia and other : aquatic invertebrates (Acute toxicity)	Remarks: Based on available data, the classification criteria are not met. Practically non toxic:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

ersion 2	Revision Date: 02/17/2023		0S Number: 0010035729	Print Date: 04/29/2023 Date of last issue: 01/05/2022
			LL/EL/IL50 > 10	0 mg/l
Toxic icity)	ity to algae (Acute tox-	:	Remarks: Based are not met. Practically non t LL/EL/IL50 > 10	
Toxic icity)	ity to fish (Chronic tox-	:	Remarks: Based are not met.	d on available data, the classification criteria
	ity to daphnia and other tic invertebrates (Chron- icity)	:	Remarks: Based are not met.	d on available data, the classification criteria
	ity to microorganisms e toxicity)	:	Remarks: Based are not met.	d on available data, the classification criteria
<u>Com</u>	ponents:			
	ole derivative: ctor (Acute aquatic tox-	:	1	
M-Fa toxicit	ctor (Chronic aquatic ty)	:	1	
Persi	stence and degradabili	ity		
Prod	uct:			
	egradability	:	Major constituer components tha Persistent per II International Oil tion: "A non-per- consists of hydr by volume, disti at least 95% of 370°C (700°F) v	eadily biodegradable. Ints are inherently biodegradable, but contains at may persist in the environment. MO criteria. Pollution Compensation (IOPC) Fund defini- sistent oil is oil, which, at the time of shipmen ocarbon fractions, (a) at least 50% of which, Ils at a temperature of 340°C (645°F) and (b) which, by volume, distils at a temperature of when tested by the ASTM Method D-86/78 or revision thereof."
Biood	ccumulative potential			
Diua				
Prod	uct:			
Prod	<u>uct:</u> cumulation	:	Remarks: Conta cumulate.	ains components with the potential to bioac-
<u>Prod</u> i Bioac		:		ains components with the potential to bioac-
<u>Prod</u> i Bioac	ity in soil	:		ains components with the potential to bioac-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Revision Date: 02/17/2023	SDS Number: 800010035729	Print Date: 04/29/2023 Date of last issue: 01/05/2022
	If it enters soil, mobile.	it will adsorb to soil particles and will not be
	Remarks: Float	s on water.
r adverse effects		
uct:		
ional ecological infor- n	ozone creation Product is a mi be released to	ozone depletion potential, photochemical potential or global warming potential. xture of non-volatile components, which will not air in any significant quantities under normal se.
	2	nixture. al fouling of aquatic organisms.
i	02/17/2023	02/17/2023 800010035729 If it enters soil, mobile. Remarks: Float r adverse effects uct: onal ecological infor- n Does not have ozone creation Product is a mit be released to a conditions of us Poorly soluble r

Disposal methods

Waste from residues :	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
	fical aspects at controlling polititions from ships.
Contaminated packaging :	Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation	
Remarks :	Disposal should be in accordance with applicable regional, national, and local laws and regulations.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Version	Revision Date:	SDS Number:
1.2	02/17/2023	800010035729

Print Date: 04/29/2023 Date of last issue: 01/05/2022

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
2-methylpropan-1-ol	78-83-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Version	Revision Date:	SDS Number:	Print Date: 04/29/2023
1.2	02/17/2023	800010035729	Date of last issue: 01/05/2022

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Zinc dialkyldithiophosphate	2215-35-2
Zinc dialkyl dithiophosphate	84605-29-8
Distillates (petroleum), hydrotreated light	64742-47-8

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

California List of Hazardous Substances

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0

California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

REACH	:	All components listed or polymer exempt.
TSCA	:	All components listed.
DSL	:	All components listed.

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

Full text of other abbreviations

Abbreviations and Acronyms	: The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
	ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.2	Revision Date: 02/17/2023	SDS Number: 800010035729	Print Date: 04/29/2023 Date of last issue: 01/05/2022
		ASTM = Ameri	can Society for Testing and Materials
			al exposure limits
			ene, Toluene, Ethylbenzene, Xylenes
			al Abstracts Service
			ean Chemical Industry Council ation Packaging and Labelling
		COC = Clevela	
			es Institut fur Normung
			d Minimal Effect Level
			d No Effect Level
			Domestic Substance List
		EC = Europear	e Concentration fifty
			ropean Center on Ecotoxicology and Toxicolo
		gy Of Chemica	
		0,	ean Chemicals Agency
		EINECS = The	European Inventory of Existing Commercial
		Chemical Subs	
		EL50 = Effectiv	
		Inventory	ese Existing and New Chemical Substances
			an Waste Code
			/ Harmonised System of Classification and
		Labelling of Ch	
			tional Agency for Research on Cancer
			ional Air Transport Association
			ry Concentration fifty
		IL50 = Inhibitor	ational Maritime Dangerous Goods
			Chemicals Inventory
			te of Petroleum test method N° 346 for the
			of polycyclic aromatics DMSO-extractables
			Existing Chemicals Inventory
			Concentration fifty
			Dose fifty per cent. al Loading/Effective Loading/Inhibitory loadin
		LL50 = Lethal L	
			ernational Convention for the Prevention of
		Pollution From	Ships
			No Observed Effect Concentration / No Ob-
		served Effect L	
			cupational Exposure - High Production Volum nt, Bioaccumulative and Toxic
			pine Inventory of Chemicals and Chemical
		Substances	
			ted No Effect Concentration
			stration Evaluation And Authorisation Of
		Chemicals	
			ons Relating to International Carriage of Dan-
		gerous Goods	by Rail kin Designation
			erm exposure limit
			d Risk Assessment
		0	xic Substances Control Act
			eighted Average

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Tellus S4 VK 46

Version	Revision Date:	SDS Number:	Print Date: 04/29/2023
1.2	02/17/2023	800010035729	Date of last issue: 01/05/2022
		vPvB = very Persistent and very Bioaccumulative	

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
Revision Date	:	02/17/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN