



SAFETY DATA SHEET

SDS ID NO.: 0173MAR019

Revision date 04/25/2023

1. IDENTIFICATION

Product Name Marathon Multipurpose 80W90 and 85W140 Gear Oils

Synonym Marathon 571 Multipurpose 80W-90 Gear Oil; 573 Multipurpose 85W-140 Gear Oil

Product code 0173MAR019

Chemical family Motor/Lube Oil

Recommended use Gear Oil.

Restrictions on use All others.

Manufacturer, Importer, or Responsible Party Name and Address
MARATHON PETROLEUM COMPANY LP
539 South Main Street
Findlay, OH 45840

SDS information 1-419-421-3070 (M-F; 8-5 EST)

24 Hour Emergency Telephone CHEMTREC: 1-800-424-9300 (CCN# 13740)

2. HAZARD IDENTIFICATION

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Classification

Skin sensitization	Category 1
--------------------	------------

Hazards Not Otherwise Classified (HNOC)

Not applicable

2.2. Label Elements

Warning

May cause an allergic skin reaction.



Appearance Yellow to amber liquid

Physical State Liquid

Odor Petroleum

Precautionary Statements - Prevention

Avoid breathing mist/vapors/spray

Wear protective gloves

Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

If on skin: Wash with plenty of soap and water
 If skin irritation or rash occurs: Get medical attention
 Wash contaminated clothing before reuse

Precautionary Statements - Storage

Not applicable

Precautionary Statements - Disposal

Dispose of contents/container at an approved waste disposal plant

Additional Information

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition Information

Chemical Name	CAS Number	% Concentration
Residual Oils (Petroleum), Solvent Dewaxed	64742-62-7	65-85
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	60-80
Distillates (Petroleum), Solvent-Refined Heavy Paraffinic	64741-88-4	3-7
Olefin Sulfide	Proprietary	1-5

Lube oil is a complex mixture of highly refined lubricating oil base stocks and additives. All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

4. FIRST AID MEASURES

First aid measures

- General advice** In case of accident or if you feel unwell, seek medical advice immediately (show directions for use or safety data sheet if possible).
- Inhalation** Remove to fresh air and keep at rest in a position comfortable for breathing. If symptoms occur get medical attention.
- Skin contact** Wash skin with plenty of soap and water. Remove contaminated clothing. Get medical attention if irritation or rash occurs. Wash contaminated clothing and clean shoes before reuse. Any injection injury from high pressure equipment should be evaluated immediately by a physician as potentially serious (See NOTES TO PHYSICIAN).
- Eye contact** Immediately flush eyes with plenty of water. Eyelids should be held away from the eyeball to ensure thorough rinsing. Gently remove contacts while flushing. If irritation or other symptoms occur get medical attention.
- Ingestion** Rinse mouth out with water. Do not induce vomiting unless directed by a physician. If spontaneous vomiting occurs, keep head below hips, or if patient is lying down, turn body and head to side to prevent aspiration and monitor for breathing difficulty. If symptoms develop, seek medical attention.

Most important signs and symptoms, both short-term and delayed with overexposure

- Adverse effects** May cause skin irritation and/or rash. Symptoms may include redness, itching, and inflammation. Prolonged or repeated inhalation of oil mist at high concentrations may cause respiratory irritation and/or other pulmonary effects. Prolonged and repeated skin contact may cause defatting and drying of the skin and may lead to irritation and/or

dermatitis.

Indication of any immediate medical attention and special treatment needed

Notes to physician SKIN: Leaks or accidents involving high-pressure equipment may inject a stream of material through the skin and initially produce an injury that may not appear serious. Only a small puncture wound may appear on the skin surface but, without proper treatment and depending on the nature, original pressure, volume, and location of the injected material, can compromise blood supply to an affected body part. Prompt surgical debridement of the wound may be necessary to prevent irreversible loss of function and/or the affected body part. High pressure injection injuries may be SERIOUS SURGICAL EMERGENCIES.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media For small fires, Class B fire extinguishing media such as CO2, dry chemical, foam or water spray can be used. For large fires, water spray, fog or foam can be used. Firefighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical The product is not combustible per the OSHA Hazard Communication Standard, but will ignite and burn at temperatures exceeding the flash point.

Hazardous combustion products Smoke, carbon monoxide, and other products of incomplete combustion.

Explosion data
Sensitivity to mechanical impact: No.
Sensitivity to static discharge: No.

Special protective equipment and precautions for firefighters Avoid using straight water streams. Water spray and foam must be applied carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Use water spray to cool exposed surfaces from as far a distance as possible. Keep run-off water out of sewers and water sources.

Additional firefighting tactics Not applicable

NFPA Health 1 Flammability 1 Instability 0 Special Hazard -

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Keep people away from and upwind of spill/leak. Contaminated surfaces may be slippery.

Protective equipment Use personal protection measures as recommended in Section 8.

Emergency procedures Advise authorities and National Response Center (800-424-8802) if the product has entered a water course or sewer. Notify local health and pollution control agencies, if appropriate.

Environmental precautions Avoid release to the environment. Avoid subsoil penetration.

Methods and materials for containment Stop leak if you can do it without risk. Prevent spilled material from entering storm drains, sewers, and open waterways. Move containers from spill area. Contain liquid with sand or soil. Contain liquid with sand or soil.

Methods and materials for cleaning up Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual liquids. Recover and return free product to proper containers. Dispose of in accordance with local/regional/national regulations.

7. HANDLING AND STORAGE

Safe handling precautions	<p>Avoid contact with skin, eyes and clothing. Do not swallow. Avoid breathing vapors or mists. Use good personal hygiene practices. Wash thoroughly after handling. Use personal protection measures as recommended in Section 8. Do not cut, drill, grind, puncture, weld or incinerate container. Empty container may contain hazardous residue. Refer to applicable EPA, OSHA, NFPA and consistent state and local requirements.</p> <p>High-pressure injection of any material through the skin is a serious medical emergency even though the small entrance wound at the injection site may not initially appear serious. These injection injuries can occur from high-pressure equipment such as paint spray or grease or guns, fuel injectors, or pinhole leaks in hoses or hydraulic lines and should all be considered serious. High pressure injection injuries may be SERIOUS SURGICAL EMERGENCIES (See First Aid Section 4).</p>
Storage conditions	<p>Store in properly closed containers that are appropriately labeled and in a cool, well-ventilated area. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from incompatible materials.</p>
Incompatible materials	<p>Strong oxidizing agents.</p>

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical Name	ACGIH TLV	OSHA PELs	NIOSH IDLH
Petroleum Base Oils MIXTURE	Highly and severely refined, inhalable fraction 5 mg/m ³ TWA	TWA: 5 mg/m ³	2500 mg/m ³

Notes: No further information available.

Engineering measures	<p>Local or general exhaust required when using at elevated temperatures that generate vapors or mists.</p>
<u>Personal protective equipment</u>	
Eye protection	<p>Use goggles or face-shield if the potential for splashing exists.</p>
Skin and body protection	<p>Wear neoprene, nitrile or PVA gloves to prevent skin contact. Glove suitability is based on workplace conditions and usage. Contact the glove manufacturer for specific advice on glove selection and breakthrough times. Wear appropriate protective clothing.</p>
Respiratory protection	<p>Use a NIOSH approved organic vapor chemical cartridge or supplied air respirators when there is the potential for airborne exposures to exceed permissible exposure limits or if excessive vapors are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 29 CFR 1910.134. Self-contained breathing apparatus should be used for fire fighting.</p>
Hygiene measures	<p>Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.</p>

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Yellow to amber liquid
Physical State	Liquid
Color	Yellow to amber

Odor	Petroleum
Odor Threshold	No data available.
Property	Values (method)
pH	No available data.
Melting Point / Freezing Point	No data available.
Initial Boiling Point / Boiling Range	No data available.
Flash Point	> 180 °C / > 356 °F (Cleveland Open-Cup)
Evaporation Rate	No data available.
Flammability (solid, gas)	Not applicable.
Flammability Limit in Air (%):	
Upper Flammability Limit:	No data available.
Lower Flammability Limit:	No data available.
Explosion Limits	No data available.
Vapor Pressure	No data available.
Vapor Density	No data available.
Specific Gravity / Relative Density	0.91 (0.88-0.91)
Water Solubility	No data available.
Partition Coefficient	No data available.
Autoignition Temperature	No data available.
Decomposition Temperature	No data available.
Kinematic Viscosity	> 100 cSt @ 40°C / 104°F
VOC Content (%)	No data available.

10. STABILITY AND REACTIVITY

Reactivity	The product is non-reactive under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	None under normal processing.
Hazardous polymerization	Will not occur.
Conditions to avoid	Sources of heat or ignition.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	None known under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Potential short-term adverse effects from overexposures

Inhalation	Inhalation of high vapor concentrations may cause irritation of the respiratory system.
Eye contact	Exposure to vapor or contact with liquid may cause mild eye irritation, including tearing, stinging, and redness.
Skin contact	May cause an allergic skin reaction. Prolonged or repeated exposure may cause dermatitis, folliculitis or oil acne.
Ingestion	May cause irritation of the mouth, throat and gastrointestinal tract.

Acute toxicological data

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum Base Oils MIXTURE	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5 mg/L (Rat) 4 h

Immediate and delayed effects as well as chronic effects from short and long-term exposure

BASE OILS: Mineral oil mists from highly refined or hydrotreated oils are generally of low acute and subchronic toxicity. Overexposure to mists may cause inflammation of the lungs and lipid pneumonia.

Adverse effects related to the physical, chemical and toxicological characteristics

Signs and symptoms	May cause sensitization by skin contact. Symptoms may include redness, itching, and inflammation. Prolonged or repeated inhalation of oil mist at high concentrations may cause respiratory irritation and/or other pulmonary effects. Prolonged and repeated skin contact may cause defatting and drying of the skin and may lead to irritation and/or dermatitis. May cause skin irritation and/or rash.
Acute toxicity	None known.
Skin corrosion/irritation	None known.
Serious eye damage/eye irritation	None known.
Sensitization	May cause sensitization by skin contact. Not expected to be a respiratory sensitizer.
Mutagenic effects	None known.
Carcinogenicity	Prolonged or repeated contact with used lube oils may cause skin cancer.

Chemical Name	ACGIH (Class)	IARC (Class)	NTP	OSHA
Petroleum Base Oils MIXTURE	Mineral oil, highly/severely refined (inhalable fraction) Not Classifiable (A4)	Mineral oil, highly refined Not Classifiable (3)	Not Listed	Not Listed

Reproductive toxicity	None known.
Specific Target Organ Toxicity (STOT) - single exposure	None known.
Specific Target Organ Toxicity (STOT) - repeated exposure	None known.
Aspiration hazard	None known.

12. ECOLOGICAL INFORMATION

Ecotoxicity Used motor and/or lube oils may be toxic to birds and fish.

Chemical Name	Fish	Crustacea	Algae/aquatic plants
Petroleum Base Oils MIXTURE	96-hr LC50 = 5000 mg/L Rainbow trout	48-hr EC50 = 1000 mg/L Daphnia magna	-

Persistence and degradability	Not expected to be readily biodegradable.
Bioaccumulation	No information available.
Mobility in soil	No information available.
Other adverse effects	No information available.

13. DISPOSAL CONSIDERATIONS

Description of waste residues	No information available.
Safe handling of wastes	Handle in accordance with applicable local, state, and federal regulations. Use personal protection measures as required.
Disposal of wastes / methods of disposal	The user is responsible for determining if any discarded material is a hazardous waste (40 CFR 262.11). Dispose of in accordance with federal, state and local regulations.
Contaminated packaging disposal	Empty containers should be completely drained and then discarded or recycled, if possible. Do not cut, drill, grind or weld on empty containers since explosive residues may be present. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT

UN/Identification No:	Not applicable
UN Proper Shipping Name:	Not Regulated
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable

IATA

UN/Identification No:	Not applicable
UN Proper Shipping Name:	Not Regulated
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable

IMDG

UN/Identification No:	Not applicable
UN Proper Shipping Name:	Not Regulated
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable

15. REGULATORY INFORMATION

Regulatory Information

US TSCA Chemical Inventory	This product and/or its components are listed on the TSCA Chemical Inventory or are exempt.
Canada DSL/NDSL Inventory	This product and/or its components are listed either on the Domestic Substances List (DSL) or are exempt.
EPA Superfund Amendment & Reauthorization Act (SARA)	
SARA Section 302	This product does not contain any component(s) included on EPA's Extremely Hazardous Substance (EHS) List above the de minimis threshold.
SARA Section 304	This product does not contain any component(s) identified as an EHS or a CERCLA Hazardous substance above the de minimis threshold.
SARA Section 311/312	The following EPA hazard categories apply to this product: Respiratory or Skin sensitization
SARA Section 313	This product does not contain components, which if in exceedance of the de minimus threshold, may be subject to the reporting requirements of SARA Title III Section 313 Toxic Release Reporting (Form R).

U.S. State Regulations

California Proposition 65

This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm.

Chemical Name	California Proposition 65
Methyl Isobutyl Ketone 108-10-1	Carcinogen, initial date 11/04/2011 Developmental toxicity, initial date 03/28/2014
1,4-dioxane 123-91-1	Carcinogen, initial date 01/01/1988
Ethyl Acrylate 140-88-5	Carcinogen, initial date 07/01/1989
Ethylene Oxide 75-21-8	Carcinogen, initial date 07/01/1987 Developmental toxicity, initial date 08/07/2009 Reproductive toxicity, initial date (female) 02/27/1987 - (male) 08/07/2009
Propylene Oxide 75-56-9	Carcinogen, initial date 10/1/1988

For more information, go to www.P65Warnings.ca.gov.

State Right-To-Know Regulations The following component(s) of this material are identified on the regulatory lists below:


Chemical Name	New Jersey Right-To-Know	Pennsylvania Right-To-Know	Massachusetts Right-To-Know
Petroleum Base Oils MIXTURE	Listed	Listed	Listed

16. OTHER INFORMATION

Prepared by

Toxicology & Product Safety

NFPA



Revision Notes

Revision date 04/25/2023
Previous publish date 11/06/2017
Revised sections 1. IDENTIFICATION
 3. COMPOSITION/INFORMATION ON INGREDIENTS
 4. FIRST AID MEASURES
 7. HANDLING AND STORAGE
 11. TOXICOLOGICAL INFORMATION
 15. REGULATORY INFORMATION

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is intended as guidance for safe handling, use, processing, storage, transportation, accidental release, clean-up and disposal and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

