

SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

QUARTZ RACING 10W-60

SDS # : 080418

Section 1. Identification

GHS product identifier

: QUARTZ RACING 10W-60

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Engine oil	

Supplier's details

: TotalEnergies Marketing USA, Inc. 1201 Louisiana St. Suite 1800 Houston, TX 77002 Phone: 713-483-5000 ProductSafety@totalenergies.com

VotalEnergies Marketing Puerto Rico Corp Millennium Park Plaza, #15 Road 2, Suite 525 Guaynabo, P.R. 00968 Phone: 1-787-783-4625

Emergency telephone number (with hours of operation)

1-866-928-0789 (For Emergencies, call CARECHEM 24/7 Domestic) 1-215-207-0061 (For Emergencies, call CARECHEM 24/7 International)

Section 2. Hazards identification

ŝ

OSHA/HCS status	: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	: Not classified.
GHS label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.
Hazards not otherwise classified	: None known.



SDS #: 080418

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	% (w/w)	CAS number
Sistillates (petroleum), hydrotreated light paraffinic	≤10	64742-55-8
Distillates (petroleum), hydrotreated heavy paraffinic	≤5	64742-54-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Additional : Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346 The product is made from synthetic base oils

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important sympt	oms/effects, acute and delayed	
Potential acute healt	h effects	
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.	
Ingestion	: No known significant effects or critical hazards.	
Over-exposure signs	s/symptoms	
Eye contact	: No specific data.	
Inhalation	: No specific data.	
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking	
Ingestion	: No specific data.	
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. 	

Date of revision : 2022/11/22



SDS #: 080418

training.

Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: carbon monoxide carbon dioxide Silicon Dioxide nitrogen oxides phosphorus oxides sulfur oxides Hydrogen sulfide Mercaptans Zinc oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	1	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and

place in an appropriate waste disposal container. Dispose of via a licensed waste

disposal contractor.



SDS #: 080418

Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact
	information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Advice on general occupational hygiene	 Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits	
Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated light paraffinic	ACGIH TLV (United States, 1/2021). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 1/2021). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2020). [OIL
	MIST MINERAL] TWA: 5 mg/m ³ 10 hours. Form: Mist
	STEL: 10 mg/m ³ 15 minutes. Form: Mist
	OSHA PEL (United States, 5/2018). [Oil mist, mineral]
	TWA: 5 mg/m ³ 8 hours.



SDS # : 080418

Advisory OEL	 Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH (TLV) TWA 5 mg/m3 (highly refined)
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	 Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Hydrocarbon-proof gloves Fluorinated rubber nitrile rubber Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: None under normal use conditions If these are not sufficient to maintain exposure below the OEL, suitable respiratory protection must be worn

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

Appearance

Date of revision : 2022/11/22	1.02	USA	ENG
Flash point	: Øpen cup: 220°C (428°F) [Cleveland Open Cup (COC)]		
Boiling point	: ₱316°C (>600.8°F) [ISO 3405]		
Melting point/freezing point	: 🔽 echnically not possible to measure		
рН	: Not applicable.		
Odor threshold	: Not available.		
Odor	: Characteristic.		
Color	: Yellow.		
Physical state	: Liquid. [limpid]		
Appearance			



SDS #: 080418

Evaporation rate	: N	lot available.
Flammability (solid, gas)	: 📐	ot applicable.
Lower and upper explosive (flammable) limits		ower: 0.9% Jpper: 7%
Vapor pressure		0.013 kPa (<0.1 mm Hg) [room temperature] lot applicable. [50°C]
Vapor density	: >	2 [Air = 1]
Relative density	: 0	.838 to 0.858 [ISO 12185]
Density	: Ø	
Solubility(ies)	:	
Media		Result
water		Not soluble
Miscible with water	: N	 lo.
Partition coefficient: n- octanol/water	: N	lot applicable.
Auto-ignition temperature	: >	220°C (>428°F) [ASTM E 659]
Decomposition temperature	: 📐	ot applicable.
Viscosity	:	(inematic (40°C (104°F)): 184 mm²/s (184 cSt) [ISO 3104]
Flow time (ISO 2431)	: N	lot available.
Particle characteristics		
Median particle size	:	Not applicable.
Section 10. Stabili	ty a	and reactivity
Reactivity	: N	lo specific test data related to reactivity available for this product or its ingredients.

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: carbon monoxide carbon dioxide Silicon Dioxide nitrogen oxides phosphorus oxides sulfur oxides Hydrogen sulfide Mercaptans Zinc oxides



SDS # : 080418

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity		1			
Product/substance	Result	Species	Dose	Exposure	Test
Distillates (petroleum),	LC50 Inhalation Dusts	Rat	>5 mg/l	4 hours	OECD 403
hydrotreated light paraffinic	and mists LD50 Dermal	Rabbit	>5000 mg/kg		OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 402 OECD 420
Distillates (petroleum),	LC50 Inhalation Dusts	Rat - Male,	>5 mg/l	4 hours	OECD 403
hydrotreated heavy paraffinic		Female			Read across
	LD50 Dermal	Rabbit - Male,	>5000 mg/kg	-	OECD 402
	LD50 Oral	Female Rat - Male,	>5000 mg/kg		Read across OECD 401
		Female	s oooo mg/ng		Read across
Conclusion/Summary	: Based on available data	, the classification	n criteria are not	t met.	
Irritation/Corrosion					
Skin	: Based on available data, t	the classification	criteria are not i	met.	
Eyes	: Based on available data, t	the classification	criteria are not i	met.	
Respiratory	: Based on available data, t	the classification	criteria are not i	met.	
Sensitization					
Skin	: Based on available data,				
Respiratory	: Based on available data,	the classification	i criteria are not	met.	
<u>Mutagenicity</u>					
Conclusion/Summary	: Based on available data, t	the classification	criteria are not i	met.	
Carcinogenicity					
Conclusion/Summary	: Based on available data, t	the classification	criteria are not i	met.	
Reproductive toxicity					
Conclusion/Summary	: Based on available data, t	the classification	criteria are not i	met.	
Teratogenicity					
Conclusion/Summary	: Based on available data,	the classification	i criteria are not	met.	
Specific target organ toxicit					
Conclusion/Summary	: Based on available data,	the classification	criteria are not	met.	
Specific target organ toxicit	_				
Conclusion/Summary	: Based on available data	, the classification	n criteria are not	t met.	
Aspiration hazard					
Name			Result	··· ··· ······························	
Distillates (petroleum), hydrot Distillates (petroleum), hydrot			ASPIRATION ASPIRATION		
Conclusion/Summary	: Based on available data	, the classification	n criteria are not	t met.	
nformation on the likely outes of exposure	: Not available.				
otential acute health effects	1				
Eye contact	: No known significant effe	ects or critical ha	zards.		
Inhalation	: No known significant effe	ects or critical ha	zards.		
Skin contact	: Defatting to the skin. Ma	ay cause skin dry	ness and irritati	on.	
ate of revision : 2022/11/22	1.02			USA	ENGLISH 7/2



SDS # :

080418

		000 // 000 //
Ingestion	No known significant effects or critical hazards.	
Symptoms related to the phy	cal, chemical and toxicological characteristics	
Eye contact	No specific data.	
Inhalation	No specific data.	
Skin contact	Adverse symptoms may include the following: irritation dryness cracking	
Ingestion	No specific data.	
Delayed and immediate effe	and also chronic effects from short and long term expo	<u>osure</u>
Short term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Long term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Potential chronic health eff	<u>ts</u>	
Not available.		
General	No known significant effects or critical hazards.	
Carcinogenicity	During use in engines, contamination of oil with low levels occurs. Used motor oils have been shown to cause skin or repeated application and continuous exposure. Brief or in used motor oil is not expected to have serious effects in h removed by washing with soap and water.	cancer in mice following ntermittent skin contact with
Mutagenicity	No known significant effects or critical hazards.	
Reproductive toxicity	No known significant effects or critical hazards.	
Numerical measures of toxic	L	

Numerical measures of toxicity

Acute toxicity estimates

N/A

Section 12. Ecological information

<u>Toxicity</u>				
Product/substance	Result	Species	Exposure	Test
Distillates (petroleum), hydrotreated light paraffinic	Acute EC50 >100 mg/l	Algae - Pseudokirchnerella subcapitata	48 hours	OECD 201
, <u> </u>	Acute EC50 >10000 mg/l	Daphnia - Daphnia magna	48 hours	OECD 202
	Chronic NOEL 10 mg/l	Daphnia - Daphnia magna	21 days	OECD 211
	Chronic NOEL >1000 mg/l	Fish - Oncorhynchus mykiss	21 days	-
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Acute EC50 >10000 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
Date of revision : 2022/11/22	1.02		USA	ENGLISH 8/1



SDS # : 080418

5	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
Chronic NOEL >1000 mg/l	Crustaceans - Daphnia magna	21 days	-

Persistence and degradability

Product/substance	Test	Result		Dose	Inoculum
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F	31 % - Not readily -	28 days	-	Activated sludge
Product/substance	Aquatic half-life		Photolysis		Biodegradability
₱istillates (petroleum), hydrotreated heavy paraffinic	-		-		Not readily

Bioaccumulative potential

Product/substance	LogK _{ow}	BCF	Potential
₱fistillates (petroleum), hydrotreated heavy paraffinic	>4	-	high

Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility in soil	: Given its physical and chemical characteristics, the product generally shows low soil mobility The product is insoluble and floats on water Loss by evaporation is limited

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any
	regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid
	dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	ICAO/IATA
UN/ID No	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Date of revision :	2022/11/22 1.	02	USA ENGLISH 9/*



SDS # : 080418

Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information			

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

U.S. Federal regulations	: те	SCA 8(a) PAIR: dip	ohenylamine; Siloxanes and Silicones, di-Me
	Т	TSCA 8(a) CDR Exempt/Partial exemption: Not determined	
	(p		WA) 307: zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis); Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: No	ot listed	
Clean Air Act Section 602 Class I Substances	: No	ot listed	
Clean Air Act Section 602 Class II Substances	: No	ot listed	
DEA List I Chemicals (Precursor Chemicals)	: No	ot listed	
DEA List II Chemicals (Essential Chemicals)	: No	ot listed	
SARA 302/304			
Composition/information	<u>on ing</u>	<u>redients</u>	
No products were found.			
SARA 304 RQ	: No	ot applicable.	
<u>SARA 311/312</u>			
Classification	: Not	applicable.	
Composition/information	<u>on ing</u>	<u>redients</u>	
Name		%	Classification
Distillates (petroleum), hydrotreated light paraffinic	;	≤10	ASPIRATION HAZARD - Category 1

hydrotreated heavy paraffinic State regulations Massachusetts : The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFINIC; OIL MIST, MINERAL New York : None of the components are listed. New Jerson : None of the components are listed.

≤5

Distillates (petroleum),

New Jersey		: None of the components are listed.			
Date of revision	: 2022/11/22	1.02	USA	ENGLISH	10/12

ASPIRATION HAZARD - Category 1



SDS # : 080418

Pennsylvania

: None of the components are listed.

California Prop. 65

To the best of our knowledge, this product does not contain any substances known to the State of California to cause cancer, developmental and/or reproductive harm

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.


Inventory list

Australia inventory (AIIC)	: All components are listed or exempted.
Canada inventory (DSL/NDSL)	: All components are listed or exempted.
China inventory (IECSC)	: All components are listed or exempted.
Europe inventory (EC)	: 🕅 components are listed or exempted.
Japan inventory	 Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC)	: 🕅 components are listed or exempted.
Philippines inventory (PICCS)	: Not determined.
Korea inventory (KECI)	: 🕅 components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	: 🕅 components are listed or exempted.
Thailand inventory	: Not determined.
Turkey inventory	: Not determined.
United States inventory (TSCA 8b)	: All components are listed or exempted.
Vietnam inventory	: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

Section 16. Other information

Hazardous Material Information System (U.S.A.)





SDS #: 080418

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

	Classification	Justification
Not classified.		
History		
Date of revision	: 2022/11/22	
Date of previous revision	: 2022/05/25	
Version	: 1.02	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification a IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeff MARPOL = International Convention for the Prevention as modified by the Protocol of 1978. ("Marpol" = marin N/A = Not available SGG = Segregation Group UN = United Nations	ficient n of Pollution From Ships, 1973
References	: Not available.	

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.