



A HOLLYFRONTIER BRAND

TECH DATA

PETROGLIDE™

SAW GUIDE OILS

INTRODUCTION

Petro-Canada's PETROGLIDE oils are premium quality saw guide oils specially designed and tested for modern multi-blade, gang saws and edgers. PETROGLIDE is formulated to provide optimum tackiness and reduced friction for increased recovery rates and sawmill productivity.

Petro-Canada's family of PETROGLIDE products starts with the HT purity process to produce a 99.9% pure, crystal clear base oil – some of the purest in the world. By removing the impurities that can hinder performance, and blending in our specialty additives, PETROGLIDE delivers maximum performance.

FEATURES AND BENEFITS

SUPERIOR TACKINESS

Less wash off and better lubricity

- Reduces oil consumption, pitch build-up, energy costs, heat build-up and saw deviation
- Helps increase productivity, save money and contribute to greater sawmill profitability
- Only Petro-Canada monitors and indicates the level of tackiness for each grade in the PetroGlide family

GREATER RECOVERY WITH SUPERIOR EXTREME PRESSURE PROPERTIES

Reduces friction and metal-to-metal contact

- Helps reduce wear and heat build-up for both saw guides and blades, minimizing saw deviation and maximizing recovery
- Fewer saw and guide changes, longer cutting cycles, less unscheduled maintenance and lower operating costs

Environmentally Friendly

- Inherently biodegradable
- Dioxin formation and environmental concerns are reduced due to low levels of dioxin precursors

Other Features

- Outstanding water separation reduces oil wash-off
- Anti-rust additive keeps blades cleaner helping to increase saw life

APPLICATIONS

Petro-Canada's PETROGLIDE saw guide oils are specially formulated to lubricate the multiple saws and guides of modern arbor edgers. PETROGLIDE 100 and 150 are recommended for use in arbor edgers (horizontal, vertical, single or double configurations), curve saws and thin kerf gang- saws manufactured by Ukiah, Kockums-Cancar, Schurman, Newnes, Optimil, McGehee, and CAE.

TYPICAL PERFORMANCE DATA

| Property | Test Method | PETROGLIDE | |
|--|-------------|--------------|--------------|
| | | 100 | 150 |
| Density, kg/L @ 15°C | ASTM D4052 | 0.864 | 0.878 |
| Viscosity, cSt @ 40°C cSt @ 100°C | ASTM D445 | 110 14.0 | 175 18.2 |
| Viscosity Index | ASTM D2270 | 128 | 115 |
| Flash Point, °C / °F | ASTM D92 | 268 / 514 | 270 / 518 |
| Pour Point, °C / °F | ASTM D5950 | -36 / -33 | -33 / -27 |
| Four Ball EP Weld Load, kg | ASTM D2783 | 200 | 200 |
| Tackiness Level, % | PCM 530 | 58 | 63 |
| Filterability Performance | PCM 531 | Pass | Pass |
| Rust Prevention, Procedure A | ASTM D665 | Pass | Pass |
| Mechanical Emulsion, 82°C, mL (minutes) | ASTM D1401 | 43-37-0(15)* | 43-37-0(15)* |
| Dibenzofuran (DBF), Dibenzodioxin (DBD), ppb | PCM 514 | 15 | 15 |

The values quoted above are typical of normal production. They do not constitute a specification.

Learn more about us: lubricants.petro-canada.com

Contact us: lubecsr@hollyfrontier.com

Committed to the disciplined operation of our business.



Petro-Canada Lubricants Inc.

2310 Lakeshore Road W. Mississauga, Ontario, Canada L5J 1K2

lubricants.petro-canada.com

Trademarks are owned or used under license.
IM-7844E (2021.04)