



A HOLLYFRONTIER BUSINESS

# TECH DATA

## SUPREME™ SYNTHETIC HYBRID

### MULTIGRADE MOTOR OILS

## INTRODUCTION

SUPREME™ SYNTHETIC HYBRID Motor Oils, are formulated to meet the demanding needs of hybrid engines. Internal combustion (IC) engines when combined with battery power go through significantly more start-ups than just a regular internal combustion engine. Engine start-up is the time in an engine's cycle where the most wear can occur. Enter SUPREME SYNTHETIC HYBRID motor oils to provide the best protection for a hybrid IC engine's unique needs. Equipped to meet the needs of a hybrid IC engine by providing exceptional lubrication of critical engine parts while providing enhanced protection for the latest emission control systems, turbochargers and gasoline direct injection IC engines.

SUPREME SYNTHETIC HYBRID Motor Oils start with a pure advantage. They are formulated using Petro-Canada Lubricants Synthetic base oils, which are among the purest base oils in the world. We use the HT Purity Process to remove performance-hindering impurities. Our base oils are 99.9% pure. That purity can help maximize the performance of our motor oils. In combination with leading-edge additive technology, they deliver exceptional resistance to thermal breakdown, outstanding low temperature fluidity, and excellent IC engine protection against wear and deposit formation under the most severe driving conditions.

SUPREME SYNTHETIC HYBRID Motor Oils are specially formulated to exceed the latest API Service Classification for gasoline engines, API SP with Resource Conserving. With available SAE 0W-20 and 0W-16 grades, they meet the needs of most hybrid vehicles.

SUPREME SYNTHETIC HYBRID Motor Oils also exceed the latest ILSAC GF-6 standards. The SAE 0W-20 grade is approved against GM's dexos1™ Gen 2 global gasoline engine oil specification to meet the warranty requirements of GM vehicles that specify a dexos1™ Gen 2 fluid.

## FEATURES AND BENEFITS

### Extended Engine Life

- Superior protection of the hybrid engine, meeting its unique needs
- Outstanding protection against wear, rust and corrosion
- Outstanding turbo-deposit control
- Bearing life greatly extended
- Minimizes wear due to stop-start driving
- Improves engine performance through excellent aeration control
- Protects against low speed pre-ignition (LSPI) and accelerated timing-chain wear in GDI/TGDI IC engines

### Our Best Resistance to High Temperature Thermal Breakdown

- Cleaner running engines
- Reduces deposits of varnish, sludge and carbon on engine parts
- Protects turbochargers from deposit formation
- Minimizes piston-ring sticking
- Improves lubrication because oil-ways stay clean

### Our Best Low Temperature Fluidity

- Permits easier unaided cold weather starts
- Reduces wear during low temperature start-up and operation

### Reduced Oil Consumption

- Low evaporation loss results in less oil top-up
- Verified seal compatibility to prevent leaks

### Compatible with High Ethanol Fuels (up to E85)

- Protects against engine corrosion
- Prevents water separation

### Protection of Exhaust Emission Control Systems

- Formulated to meet reduced phosphorus and sulphur levels, and to provide reduced phosphorus volatility in order to protect and extend the life of emission control systems

Petro-Canada Lubricants starts with the HT purity process to produce water-white, 99.9% pure base oils. The result is a range of lubricants, specialty fluids and greases that deliver maximum performance for our customers.

The dexos® specification and trademark are exclusive to General Motors, LLC.



## IMPROVED FUEL ECONOMY PERFORMANCE

SUPREME SYNTHETIC HYBRID Motor Oils meet or exceed the ILSAC GF-6 requirements for fuel economy improvement and fuel economy retention, which surpass previous generation ILSAC GF-5 motor oils. They not only provide better initial fuel economy, but they are better at maintaining it over the oil drain interval.

## APPLICATIONS

SUPREME SYNTHETIC HYBRID Motor Oils are recommended for year-round use in internal combustion gasoline hybrid engines. SUPREME SYNTHETIC HYBRID Motor Oils meet or exceed new car warranty requirements for North American and Asian vehicles where ILSAC GF-6 or API SP engine oils are recommended. They are fully back serviceable to previous ILSAC and API performance ratings including ILSAC GF-5 (SAE 0W-20 only) and API SN, SN PLUS.

SUPREME SYNTHETIC HYBRID Motor Oils are fully compatible with all other synthetic and conventional motor oils.

Always consult owner's manual to select the appropriate viscosity grade and approval level.

## PETRO-CANADA SUPREME™ SYNTHETIC HYBRID MOTOR OILS RECOMMENDED APPLICATIONS

■ Approved or Licensed    □ Meets    ● Suitable for Use

SAE Viscosity Grade	0W-16	0W-20
<b>API</b>		
SP	■	■
SP Resource Conserving	■	■
SN, SN Resource Conserving, SN PLUS*	□	□
<b>ILSAC</b>		
GF-6A		■
GF-6B	■	
GF-5*		□
<b>Chrysler</b>		
MS-6395		●
<b>Ford</b>		
WSS-M2C962-A1		□
<b>General Motors</b>		
GM dexos1™ Gen 2		■ D130BAAC024
<b>Asian OEMs</b>		
Honda, Hyundai, Kia, Mazda, Toyota	□	□

\* back-serviceable

dexos1™ Gen 2 supercedes dexos1® (First Generation), GM6094M and GM4718M.

The dexos® specification and trademark are exclusive to General Motors, LLC.

Always consult the owner's manual to select the appropriate viscosity grade and approval level for your engine.

## TYPICAL PERFORMANCE DATA

Property	ASTM Test Method	SUPREME SYNTHETIC HYBRID	
		0W-16	0W-20
Density, kg/L @ 15°C	D4052	0.845	0.845
Colour	D1500	<3.5	<3.0
Flash Point, COC, °C / °F	D92	232/450	232/450
Pour Point, °C / °F	D5950	-45 / -49	-45 / -49
Kinematic Viscosity cSt @ 40°C cSt @ 100°C	D445	40.6 7.8	44.3 8.3
Viscosity Index	D2270	164	166
Cold Cranking Viscosity, cP @ °C / °F	D5293	5300 @ -35 / -31	5500 @ -35 / -31
Borderline Pumping Viscosity, cP @ °C / °F	D4684	14600 @ -40 / -40	17400 @ -40 / -40
Volatility (Noack), % loss	D5800	11	11
Sulphated Ash, % wt.	D874	0.92	0.87
Sulphur, mass %	D4294	0.3	0.3
Phosphorus, mass %	D4951	0.08	0.08
Base Number, (BN), mg KOH/g	D2896	8	8
High-Temperature High-Shear (HTHS) Viscosity, cP @ 150°C and 1E+06/s	D4683	2.4	2.6

The values quoted above are typical of normal production. They do not constitute a specification.

---

Learn more about us: [lubricants.petro-canada.com](https://lubricants.petro-canada.com)  
Contact us: [lubecsr@petrocanadalsp.com](mailto:lubecsr@petrocanadalsp.com)

Committed to the disciplined operation of our business.



**Petro-Canada Lubricants Inc.**  
2310 Lakeshore Road W. Mississauga, Ontario, Canada L5J 1K2  
[lubricants.petro-canada.com](https://lubricants.petro-canada.com)

™ Owned or used under license.  
IM-8145E (2020.05)