


Mystik® JT-6® Synthetic Electric Motor #2 Grease

Formerly known as CITGO® Lithoplex® EM Full Synthetic Grease

OVERVIEW



- A premium quality lithium complex grease that is optimized to provide outstanding performance in electric motor applications

FEATURES & BENEFITS



- Outstanding wear protection.
- Excellent oxidation resistance.
- Protects against rust.
- Protects against corrosion in yellow metals such as copper and brass.
- Contains ISO 100 synthetic base oils.

APPLICATIONS



- Provides excellent protection in electric motor applications.
- This product is suitable for use where excellent wear protection and corrosion resistance is required.
- Suitable for use in many fill for life applications where outstanding oxidation resistance is needed.
- Consult owner's manual for proper lubricant selections.

PROPERTIES**Typical Properties for Mystik JT-6 Synthetic Electric Motor #2:**

Material Code	655429002
NLGI Grade	2
Thickener Type	Lithium Complex
Color	Blue
Texture	Smooth
Worked Penetration, ASTM D217	265-295
Dropping Point, ASTM D2265, °F(°C)	500 (260)
Rust Prevention, ASTM D1743, Rating	Pass
Copper Corrosion, ASTM D4048	1a
Emcor Rating	0,1
Oil Separation, ASTM D1742, % loss	1.76
Water Washout, ASTM D1264, % loss @ 175°F	<2%
Four-Ball Wear, ASTM D2266, mm	0.4
Four-Ball Weld, ASTM D2596, kgf	400
Base Oil Viscosity @ 40°C, cSt	100
Base Oil Viscosity @ 100°C, cSt	13.87
Viscosity Index (including oil soluble additives)	127
Oil Type	Synthetic

Mystik, JT-6 and Lithoplex are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks are the property of their respective owners.

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.