


# Mystik® Anti-Leak Industrial Oil

## OVERVIEW




- A very wide temperature range, multiple viscosity grade oil specially treated for maximum leakage resistance.
- May be used as a combination replacement for individual ISO 46, 68, and 100 grade hydraulic fluids.

## FEATURES & BENEFITS




- Fortified with antiwear, antifoam, antirust, and antioxidant stabilizer additives for long life.
- Contains a special anti-splatter additive for splash resistance and a slower drip-off rate.

## APPLICATIONS



- Primarily used as a combination replacement for individual grade hydraulic fluids.
- May also be used as a medium viscosity way oil, a winter rock drill oil, a 'non-drip' general purpose shop oil, and as a circulating oil for gears and bearings.

## PROPERTIES



### Typical Properties for Mystik Anti-Leak Industrial Oil:

Material Code	663300002
ISO Grade	100 (Recommended for 46, 68, 100)
SAE Grade	15W-40
Gravity, °API ASTM D4052	30.1
Density, lb/gal @ 60°F	7.29
Viscosity ASTM D445	
at 40°C, cSt	92.7
at 100°C, cSt	12.9
Viscosity Index ASTM D2270	137
Flash Point, COC, °F(°C) ASTM D92	400 (204)
Pour Point, °F (°C) ASTM D97	-30 (-34)
Appearance, Color	Aqua Blue

Mystik is a registered trademark protected by federal law. All other registered trademarks or trademarks are the property of their respective owners.