


Mystik[®] Curve Rail Greases

Formerly known as CITGO[®] Railroad Curve Greases

OVERVIEW




- Available as Curve Rail #1 and Curve Rail #0.
- Anhydrous calcium thickened greases formulated with graphite provide outstanding wear resistance.

FEATURES & BENEFITS



- Smooth, buttery texture provides exceptional spray characteristics.
- Flows through the applicator nozzle to provide a consistent spray which evenly coats the rail sides.
- Graphite provides outstanding wear protection.
- Anhydrous calcium thickener is extremely resistant to water, adhering to the rail, even in humid and rainy environments.

APPLICATIONS



- Curve Rail #1 stays in place in harsh summer weather.
- Curve Rail #0 provides improved flow during colder winter conditions.
- Both provide outstanding rail curve wear protection.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES



Typical Properties for Mystik Curve Rail:

	#1	#0
Material Code	655532002	655531002
NLGI Grade	1	0
Thickener Type	Anhydrous Calcium	Anhydrous Calcium
Color	Gray	Gray
Texture	Smooth, Buttery	Smooth, Buttery
Worked Penetration, ASTM D217	310-340	355-385
Solid Additives	Graphite	Graphite
Base Oil Viscosity @ 40°C, cSt	20	20

Mystik is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.