


Mystik® Terra Irrigation Engine Oil

OVERVIEW




- Specially formulated to provide lubrication in stationary engines that have been converted to natural gas fuel, such as those in LP and agricultural irrigation pump service.

FEATURES & BENEFITS




- Designed for added anti-wear protection for the valve train.
- Excellent deposit control and wear protection of pistons, rings, and liners.
- Improved oxidation and nitration resistance.
- Multi-grade formula with high viscosity index and low pour point for year-round performance.

APPLICATIONS



- For use in engines that have been converted to natural gas fuel, such as those in LP and agricultural irrigation pump service.

PROPERTIES**Typical Properties for Mystik Terra Irrigation Engine:**

Material Code	663062002
SAE Grade	15W-40
Gravity, ASTM D4052, °API	31.1
Density, lbs/gal	7.25
Flash Point, ASTM D92 (COC), °F (°C)	460 (238)
Viscosity, ASTM D445	
cSt at 40°C	106
cSt at 100°C	14.9
Viscosity Index, ASTM D2270	145
CCS Viscosity, ASTM D5293	
cP at -20°C	4,723
cP at -25°C	9,257
MRV Viscosity, ASTM D4684	
cP at -25°C	16,200
Pour Point, ASTM D97, °F (°C)	-38 (-39)
Color, ASTM D1500	3.5
Sulfated Ash, ASTM D874, m%	0.50
TBN, ASTM D2896	5.0
Zinc, ppm	900

Mystik is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.