




CITGO® HyDurance® AW All Temp NZ Fluids

OVERVIEW




- High performance, zinc-free anti-wear lubricants designed to provide outstanding protection over a wide temperature range.
- Provide outstanding protection for demanding hydraulic systems operating in environmentally sensitive areas.

FEATURES & BENEFITS




- Superior, high viscosity index, zinc-free, anti-wear hydraulic and circulating oils.
- Provide excellent resistance to sludge formation and exhibit excellent filterability.
- Can be used over a wide temperature range.
- Designed to provide maximum service life to vane, piston, and gear pumps as well as other circuit components such as motors and servos.
- Can be used as a gear and bearing oil.
- Outstanding low temperature performance.
- Excellent resistance to foaming -- will not foster abnormal air entrainment in properly designed hydraulic systems.
- Inherently biodegradable and low acute aquatic toxicity.

APPLICATIONS



- Recommended for high-pressure, high-output industrial hydraulic circuits.
- Recommended for mobile and other hydraulic equipment in heavy duty all-weather service.
- Can be used in circulating systems of machine tools, presses, air compressors, and other gear and bearing applications where rust- and oxidation-inhibited oils are required.
- Meet or exceed the stringent performance requirements of:
 - GM LS-2
 - Eaton Brochure 03-401-2010
 - DIN 51524 Part 2
 - U.S. Steel 127, 136, 126
 - Parker Denison HF-0
- Can be used in applications operating in environmentally sensitive areas where the use of a zinc-free, ashless formulated fluid is desired, such as:
 - Marine – offshore rigs, tugs, dredges, hydraulic lifts, cranes, pile-drivers (note: does not meet EPA 2013 Vessel General Permit VGP EAL requirements).
 - Forestry – scalpers, excavators, wheel loaders.
 - Construction – bulldozers, graders, backhoes.
 - Mining – conveyors, crawlers, hole drillers
- Refer to equipment owner’s manual for proper lubricant recommendation.

PROPERTIES



Typical Properties for CITGO HyDurance AW All Temp NZ Fluids:

Material Code	633612	633613	633614
ISO Vis Grade	32	46	68
Gravity, °API, ASTM D4052	34.5	33	31
Density, lbs/gal at 60°F	7.1	7.17	7.25
Specific Gravity at 60°F, ASTM D1298	0.8523	0.8602	0.8708
Flash Point (COC) , F° (C°) ASTM D92	401 (205)	403 (206)	453 (234)
Pour Point F °(C°) ASTM D97	-60 (-51)	-49 (-45)	-49 (-45)
Brookfield Viscosity ASTM D2983			
at -20°C, cP	–	2688	4650
at -30°C, cP	2260	9680	17670
at -40°C, cP	11360	–	–
Viscosity ASTM D445			
cSt at 40°C, cSt	32	46	68
cSt at 100°C, cSt	6.1	7.9	10.8
Viscosity Index, ASTM D2270	140	146	149
Water Separability, mL-mL-mL(min)ASTM, D1401 @130F°	40-40-0(15)	40-40-0(20)	40-40-0(20)
Four Ball Wear, mm D4172, 40kg	0.70	0.55	0.49
Rust Prevention ASTM D665 A/B	Pass/Pass	Pass/Pass	Pass/Pass
Copper Corrosion	1A	1A	1A
Oxidation Stability, hr ASTM D943	8000	8000	8000

CITGO and HyDurance are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.