

CO-250

High temperature chain oil



Your benefits at a glance

- Special synthetic base oil: prevents residue build-up
- High temperature stability: offers effective lubrication at high temperatures
- Low evaporation rate: minimizes oil consumption
- High wear protection: increases chain life
- Good spreadability: enables oil to penetrate extremely narrow gaps at the lubrication point

Your requirements - our solution

CO-250 was specifically developed for high temperature roller chains operating at temperatures in excess of 200 °C. CO-250 should be used for the chains, steel belts and heated press platens found in continuous particle board and wood laminate machinery.

Application

Chains, steel belts and heated press platens

Application notes

Automatic lubrication systems are recommended.

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	CO-250
Article number	340016
Density	0.902 g/cm ³
Fire point	285 °C
Flash point	266 °C
Refractive index	1.49
Kinematic viscosity, 100°C	30 mm ² /s
Kinematic viscosity, 20°C	800 mm ² /s
Kinematic viscosity, 40°C	260 mm ² /s
Viscosity index	150
Pour point	-35 °C
Four-ball tester: wear characteristics	0.3 mm
Four-ball tester, welding load	2400 N
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

CO-250

High temperature chain oil



Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsupport.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.