

January 5, 2022

Klüber Lubrication NA LP • 9010 CR 2120, Tyler, Texas 75707, Phone 903.534.8021 • sales@klsummit.com

# Product Data Sheet



NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

## SYNTHETIC AIR COMPRESSOR

### SUPRA COOLANT®

*Summit Supra Coolant® has been formulated to address the specific problems associated with conventional rotary screw compressor coolants - thermal degradation and deposit formation. The polyglycol/ester blend has proven itself superior in the areas of oxidation resistance and deposit formation. Supra Coolant® is the alternative to varnish, sludge and the frequent lubricant changes associated with hydrocarbon oils.*

### Physical Properties

PRODUCT	SUPRA COOLANT®
SAE GRADE	10W-20
Viscosity	
@ 40°C, cSt	57.3
@ 100°C, cSt	10.2
@ 100°F, SUS	279
@ 210°F, SUS	57.7
Viscosity Index	167
Specific Gravity	0.962
Flash Point, °F (°C)	510 (266)
Pour Point, °F (°C)	-59 (-50)
Density, lbs/gal	8.024
Autoignition Temp., °F (°C)	750 (399)
Conradson Carbon, % Residue	0.028
RPVOT, Min.	2300
Evaporation Loss Percentage, 22 hours @ 210°F	0.26

**Shelf Life:** Product shelf life is 5 years from the date of manufacture, after which the product should be recertified prior to use.