

February 21, 2022

Klüber Lubrication NA LP • 9010 CR 2120 Tyler, TX 75707 • Phone 903.534.8021 • sales@klsummit.com

Product Data Sheet



NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

SYNTHETIC AIR COMPRESSOR

SUPRA-26N

Summit Supra-26N has been formulated to address the specific problems associated with centrifugal compressor lubricants - thermal degradation and deposit formation. Supra-26N's polyglycol/ester blend has proven superior performance in the areas of oxidation resistance and deposit formation.

Physical Properties

PRODUCT	SUPRA-26N
Viscosity	
@ 40°C, cSt	27.2
@ 100°C, cSt	5.8
@ 100°F, SUS	136
@ 210°F, SUS	44.2
Viscosity Index	150
Specific Gravity	0.955
Flash Point, °F (°C)	446 (230)
Pour Point, °F (°C)	-72 (-58)
Density, lbs/gal	7.989

Shelf Life: Product shelf life is 5 years from the date of manufacture, after which the product should be recertified prior to use.