

PRODUCT DATA SHEET



Multipower-3 Monograde Motor Oil | Heavy Duty

Product Description

Marathon Multipower-3 Monograde are high-performance heavy-duty motor oils, ideal for older four-stroke gasoline and diesel engines¹. This product line meets the API service requirements of CF² and CF-2² / SL. Multipower-3 combines premium Group II base oils and advanced additive technology to deliver engines the best in protection where monograde viscosity is required by the OEM³.

Features

- ➔ Advanced protection against sludge build-up, corrosion, and oil degradation
- ➔ Extended deposit and wear control

SAE Grade	ASTM	10W/20W	30W	40W	50W
Product Numbers		10W: 1038 (bulk), 0212 (55 g drum), 0211 (5 G pail) 20W: 1040 (bulk), 0222 (55 g drum)	1042 (bulk), 0235 (55 g drum), 0233 (5 G pail), 0231 (4/1 gals), 0230 (12/1 qts)	1041 (bulk), 0242 (55 g drum)	1043 (bulk), 0246 (55 g drum)
Viscosity @ 100°C, cSt	D445	5.79	12.07	14.43	18.73
Viscosity @ 40°C, cSt	D445	31.02	100.30	133.40	190.50
Viscosity Index	D2770	131	111	107	110
Specific Gravity at 60°F	D4052	0.8597	0.8788	0.8822	0.8810
Pour Point, °C	D5950	-42	-33	-33	-33
Color ASTM	D1500	L3.0	L3.0	L3.0	L3.0
CCS, cP	D5293	2,500 (-25°C)	N/A	N/A	N/A
Flash Point COC °C	D92	200	220	220	245
TBN	D2896	7.1	7.2	7.0	7.2

(1) Always follow your operator's manual for recommended viscosity grade and API service classification

(2) Obsolete specifications

(3) Consult your owner's manual regarding its suitability for use in equipment from other OEMs

The recommended shelf life for these oils is typically 48 months from manufacturing date when stored properly in the original sealed containers.