

PRODUCT DATA SHEET



287 Hydraulic and Flushing Oil 5W

Product Description

Marathon 287 Hydraulic and Flushing Oil 5W is a light-bodied neutral oil, ideal in applications requiring a super thin oil. This hydraulic and flushing oil is a pure petroleum product, containing no additive metals, that boasts good low temperature properties.

Applications

Marathon 287 Hydraulic and Flushing Oil 5W has application in engine flushing, chain oil, machine oil, lubrication of certain air system types, and light duty hydraulic applications that require an SAE 5W oil or form oil.

Typical Properties	
Product Numbers	0293 (bulk), 0292 (55 g drum), 0290 (5 g pail)
Gravity API	34.0
Viscosity, cSt @ 40°C	19.8
Viscosity, cSt @ 100°C	4.05
Viscosity Index	102
Flash Point, COC, °F	390
Pour Point, °F	0

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Marathon Petroleum Company believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.