



**YOU GET OUT  
WHAT YOU  
PUT IN.** 

## Hyken® 052 Farm Tractor Lubricant

Kendall® Hyken 052 is a multi-functional fluid specially formulated for use in farm tractors and other off-highway equipment requiring one lubricant for the transmission, final drive, wet brakes and hydraulic systems. It meets the performance requirements of all major brands of farm tractors and other farm equipment that utilize a common fluid reservoir.

Hyken 052 is formulated to provide excellent oxidation resistance, excellent wear protection, protection against rust and corrosion, and resistance to foaming. It has carefully balanced frictional properties to ensure proper operation of wet brakes and transmission clutches.

Hyken 052 is available in two viscosity grades for use over a wide range of temperatures. The heavier viscosity grade is suitable for year-round use in most climates, whereas the “Low Viscosity” grade is recommended for use in cold climates where a John Deere J20D fluid is specified.

### Applications

Hyken 052 is recommended for use where the equipment manufacturer specifies:

- AGCO Power Fluid 821XL, Q-1826, Q-1802 (Type 55 Fluid), Q-1766B
- Case IH MS1210, MS1209, MS1207, MS1206
- Case New Holland (CNH) MAT3525 (134-D Fluid), MAT3506, MAT3505
- Caterpillar TO-2 (obsolete)
- Denison Hydraulics HF-0, HF-1, HF-2
- Ford ESN-M2C134-D, ESN-M2C86-C, ESN-M2C86-B, ESN-M2C41-B
- Ford-New Holland FNHA-2-C-201.00
- John Deere JDM J20C, J20D (“Low Viscosity” grade), J14C (Type 303 Fluid)
- Kubota UDT Fluid
- Landini Tractor II Hydraulic Fluid
- Massey Ferguson CMS M1145/M1143, M1141, M1135, M1129A
- Sundstrand Hydrostatic Transmission Fluid
- Vickers (Eaton) M-2950-S, I-286-S
- Volvo VME WB 101 (VCE 1273.03)
- ZF TE-ML 03E, 05F, 17E, 21F

Hyken 052 Plus also meets API GL-4 performance requirements.

**Multipurpose  
Hydraulic/  
Transmission/  
Final Drive Fluid  
for Farm Tractors**



## Features/Benefits

- Excellent oxidation resistance and thermal stability
- Excellent wear protection for clutches, gears and hydraulic pumps
- Prevents brake chatter and grabbing
- Protects against rust and corrosion
- Excellent seal compatibility
- Good foam resistance
- Two viscosity grades for use in most climates

## Hyken® 052 Farm Tractor Lubricant

Typical Properties		
Grade		Low Vis
Specific Gravity @ 60°F	0.879	0.864
Density, lbs/gal @ 60°F	7.32	7.19
Color, ASTM D1500	3.5	3.5
Flash Point (COC), °C (°F)	210 (410)	190 (374)
Pour Point, °C (°F)	-43 (-45)	-51 (-60)
Viscosity, Brookfield		
cP @ -20°C	4000	---
cP @ -35°C	26700	---
cP @ -40°C	---	11500
Viscosity, Kinematic		
cSt @ 40°C	61.0	34.3
cSt @ 100°C	9.8	7.4
Viscosity Index	146	190
Total Base Number, ASTM D2896	9.6	9.6
Zinc, wt %	0.149	0.149

## Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/SDS>

Updated: 03-10-2021

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

©Phillips 66 Company. Kendall® and its respective logos and products are registered trademarks of Phillips 66 Company in the U.S.A. and other countries.