



**YOU GET OUT
WHAT YOU
PUT IN.** 

Super Three Star[®] Synthetic Gear Lubricant

Kendall[®] Super Three Star Synthetic Gear Lubricant is a synthetic, API GL-5 automotive gear lubricant specially designed for long-drain service and extended warranty protection in passenger car and truck axles with hypoid gear sets.

Super Three Star Synthetic Gear Lubricant is formulated to provide long service life and extended gear life in automotive differentials operating under varying conditions of speed, load, temperature and torque. It combines excellent oxidation resistance and thermal stability at high temperatures with outstanding low-temperature properties to ensure excellent performance over a wide temperature range. It has excellent water-separating properties to prevent the formation of emulsions and retain its lubricating properties even in the presence of a small amount of water.

Super Three Star Synthetic Gear Lubricant is approved for 500,000-mile drain intervals in drive axles under Meritor extended warranties.

**Synthetic
Extended-Drain
Automotive Gear
Lubricant, API
GL-5/MT-1**

Applications

- Service fill of conventional differentials in passenger cars and trucks
- Top-off only of limited-slip differentials in passenger cars and light trucks ⁽¹⁾
- Service fill of differentials, final drives and transfer cases in some off-highway equipment
- Non-synchronized manual transmissions in trucks, buses and heavy equipment where the manufacturer specifies an API GL-5 or MT-1 gear oil

⁽¹⁾ **Note:** For complete drain and refill, many limited-slip differentials may require the manufacturer's specified gear lubricant or supplemental additive. Refer to the owner's manual for specific requirements.

Super Three Star meets or exceeds the requirements of:

- API Service GL-5, MT-1
- Mack GO-J
- MIL-PRF-2105E
- SAE J2360

Super Three Star is approved for service fill under the following OEM specification:

- Meritor O76-R for extended-drain lubricants



Features/Benefits

- Extended drain/extended warranty protection
- Outstanding oxidation resistance and thermal stability to minimize sludge and varnish formation
- Excellent thermal durability and extreme-pressure properties for extended gear life
- High load-carrying capacity for protection against scuffing and wear
- High shear stability
- Outstanding low-temperature properties
- Excellent water-separating properties
- Protects against rust and corrosion
- Good foam resistance
- Compatible with synthetic and conventional automotive gear oils

Super Three Star[®] Synthetic Gear Lubricant

Typical Properties		
SAE Grade	75W-90	80W-140
Specific Gravity @ 60°F	0.874	0.882
Density, lbs/gal @ 60°F	7.28	7.34
Color, ASTM D1500	L 8.0	L 8.0
Flash Point (COC), °C (°F)	200 (392)	200 (392)
Pour Point, °C (°F)	-45 (-49)	-36 (-33)
Viscosity, Brookfield		
cP @ -40°C	119,000	-----
cP @ -26°C	-----	48,000
Viscosity, Kinematic		
cSt @ 40°C	114	222
cSt @ 100°C	17.2	25.5
Viscosity Index	166	146

Health Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://www.phillips66.com/SDS>

Updated: 11-26-2019

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2016 Phillips 66 Company. Phillips 66 and its respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.