



CITGO® Calsuplex® MP Grease

OVERVIEW



- Specially formulated with a calcium sulfonate thickener in premium base oils.
- Provides excellent performance in a wide variety of automotive, heavy duty, and industrial applications.
- Provides excellent corrosion control for high moisture environments.

FEATURES & BENEFITS



- Provides superior protection against corrosion in the presence of water.
- Provides excellent extreme pressure (EP) and anti-wear protection under severe conditions.
- Provides outstanding resistance to oxidation.
- Highly resistant to water washout.
- Meets the ASTM D4950 requirements for Wheel Bearing Grease Category GC and Chassis Grease Category LB.




APPLICATIONS



- Recommended for a wide range of automotive and industrial applications including bearings, ball joints, and bushings.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES



Typical Properties for CITGO Calsuplex MP Grease:

Material Code	655582001
NLGI Grade	2
Thickener Type	Calcium Sulfonate
Color	Green
Texture	Smooth, Adhesive
Worked Penetration, ASTM D217	265-295
Dropping Point, ASTM D2265, °F(°C)	500 (260)
Rust Prevention, ASTM D1743, Rating	Pass
Water Washout, ASTM D1264, % loss @ 175°F	2.5
Low Temperature Torque, ASTM D4693, Nm	9.6
High Temperature Life, ASTM D3527, hrs.	120
Four-Ball Wear, ASTM D2266, mm	0.5
Four-Ball Weld, ASTM D2596, kgf	400
Four-Ball Load Wear Index, ASTM D2596, kgf	57.7
NLGI Certified, ASTM D4950	GC-LB
Base Oil Viscosity @ 40°C, cSt	150

CITGO and Calsuplex are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.