

# Mystik® Centra-Lube™ Grease

## OVERVIEW



- Designed as an anti-leak, industrial semi-fluid gear grease for industrial gearboxes and automatic, centralized lube systems where harder consistency greases are not pumpable in cold weather.
- Ideal for leaky gearboxes and difficult-to-service applications.

## FEATURES & BENEFITS



- Premium-quality product containing extreme pressure (EP), antiwear, antirust, and antioxidant additives.
- Self-leveling.
- Excellent wear protection and load-carrying capability.
- Outstanding water resistance protects against corrosion.
- Registered NSF H2 (125249).




Nonfood Compounds  
Program Listed H2  
Registration No. 125249

## APPLICATIONS



- Recommended for centralized lubrication systems and grease-filled gear boxes.
- For use as an industrial semi-fluid grease.
- Underground mine pressure gear systems and conveyor drive gearboxes.
- Suitable as an antileak EP gear lubricant.
- Refer to equipment owner's manual for proper lubricant recommendation.

**PROPERTIES****Typical Properties for Mystik Centra-Lube™ Grease:**

<b>Material Code</b>	<b>665023002</b>
NLGI Grade	0 to 00
Thickener Type	Lithium 12-Hydroxystearate
Texture	Smooth, Adhesive
Color	Amber
Worked Penetration, ASTM D217	380-410
Rust Prevention, ASTM D1743, rating	Pass
Copper Corrosion, ASTM D4048, rating	1b
Oxidation, ASTM D942, psi loss @ 100 hrs	2.5
Timken OK Load, ASTM D2509, lb.	60
Approximate Temperature Range, °F (°C)	0 to 250 (-18 to 121)
Base Oil: Viscosity @ 40°C, cSt	360

©2019 CITGO Petroleum Corporation

The Mystik Lubricants name, logo and all related marks are registered trademarks protected by federal law. All other registered trademarks or trademarks are the property of their respective owners.

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.