

TECHNICAL DATA SHEET



SYNTHETIC SAE 10W-40 with Moly MOTORCYCLE OIL

PRODUCT # 10777

API Service SJ, JASO MB

TEST

ASTM

TYPICAL

API Gravity	D-1298	34.2
Specific Gravity @ 60°F	D-1298	0.854
Density @ 60°F LBS/US Gal	D-1298	7.12
Viscosity @ 40°C, cSt	D-445	98
Viscosity @ 100°C, cSt	D-445	14.2
Viscosity Index	D-2270	160
Color		Amber
Flash Point, COC °F	D-92	450
CCS @ -25°C, CPS	D-5293	7,000 Max
MRV TP-1 @ -30°C, CPS	D-4684	60,000 Max

Lucas Synthetic SAE 10W-40 with Moly API SJ, JASO MB Motorcycle Oil is a blend of high quality synthetic base oils and an exclusive high performance additive package that lowers oil temperatures, extends oil and component life, reduces noise and reduces leaks.

Our unique moly chemistry provides maximum friction reducing properties in severe racing conditions. Provides wear protection at start-up and has excellent cold temperature properties. Not recommended for use in wet clutch applications. For use in all air-cooled and water/radiator cooled 4-stroke engines. **BAJA TESTED.**