



Shell Turbo Oil T 68

High Quality Industrial Steam & Gas Turbine Oils

Shell Turbo Oils T have long been regarded as the industry standard turbine oil. Building on this reputation, Shell Turbo Oils T have been developed to offer improved performance capable of meeting the demands of the most modern steam turbine systems and light duty gas turbines, which require no enhanced anti-wear performance for the gearbox. Shell Turbo Oils T are formulated from high quality hydrotreated base oils and a combination of zinc-free additives that provide excellent oxidative stability, protection against rust & corrosion, low foaming and excellent demulsibility.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

• Strong Control of Oxidation

The use of inherently oxidatively stable base oils together with an effective inhibitor package provides high resistance to oxidative degradation. The result is extended oil life, minimising the formation of aggressive corrosive acids, deposits and sludge, reducing your operating costs.

• High Resistance to Foaming and Rapid Air Release

The oils are formulated with an anti-foam additive, which generally controls foam formation. This feature coupled with fast air-release from the lubricant reduces the possibility of problems such as pump cavitation, excessive wear and premature oil oxidation, giving you increased system reliability.

• Positive Water-Shedding properties

Robust demulsibility control such that excess water, common-place in steam turbines, can be drained easily from the lubrication system, minimizing corrosion and premature wear. Lowering the risk of unplanned maintenance.

• Excellent Rust & Corrosion Protection

Prevents the formation of rust and guards against onset of corrosion ensuring protection for equipment following exposure to humidity or water during operation and during shut-downs, minimizing maintenance.

Main Applications

Shell Turbo Oils T are available in ISO grades 32, 46, 68 & 100 suited for application in the following areas:

- Industrial steam turbines & light duty gas turbines which require no enhanced anti-wear performance for the gearbox.
- Hydroelectric turbine lubrication.
- Numerous applications where strong control over rust and oxidation is required.
- Centrifugal and axial, dynamic turbo-compressors and pumps where an R&O type or turbine oil is recommended.

Specifications, Approvals & Recommendations

- Alstom HTGD 90 117 V0001 Z
- Fives Cincinnati, LLC (formerly Cincinnati Machine): P-54
- Man Turbo SP 079984 D0000 E99
- General Electric GEK 28143b
- DIN 51515-1 L-TD, 51524-1 HL
- ISO 8068:2006 - L-TGA, 8068:2006 - L-THA, 8068:2006 - L-TSA
- JIS K 2213: 2006 Type 2
- ASTM D4304-13 Type I
- GB11120-2011, L-TSA and L-TGA
- Indian Standard IS 1012:2002
- Andritz Hydro
- Siemens Turbo Compressors (spec 800 037 98)
- For special applications such as Ammonia or High Sulphur Syngas compressors with wet gas seals, please contact your local technical expert.

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical

Typical Physical Characteristics

Properties			Method	Shell Turbo Oil T 68
Viscosity	@40°C	cSt	ASTM D445	68.0
Viscosity	@100°C	cSt	ASTM D445	8.95
Viscosity Index			ASTM D2270	105
Color			ASTM D1500	L 0.5
Density	@15°C	kg/m ³	ASTM D4052	871
Pour Point		°C maximum	ASTM D97	-24
Flash Point (COC)		°C minimum	ASTM D92	240
Total Acid Number		mg KOH/g	ASTM D974	0.10
Air Release, Minutes	@50°C	minutes	ASTM D3427	5
Water Demulsibility		minutes	ASTM D1401	20
Rust Control			ASTM D665B	Pass
Oxidation Control Test - TOST Life		hours	ASTM D943	7,000+
Oxidation Control Test - RPVOT - minutes		minutes	ASTM D2272	600

These characteristics are typical of current production. While future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Turbo T 68 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

• Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell representative.