



CITGO® SUPERGARD® Air-Cooled 2-Cycle Engine Oil

OVERVIEW




- A premium-performance synthetic blend lubricant designed for use in high-performance, air-cooled two-stroke engines.
- Provides the necessary protection to keep your air-cooled, two-stroke engine running cleaner, longer, and with less smoke.

FEATURES & BENEFITS




- Engineered for lower smoke and advanced protection for air-cooled 2-cycle engines.
- Meets or exceeds the rigorous requirements of the API TC, JASO FD, and ISO-L-EGD classifications for 2-cycle air-cooled engine oils; also exceeds the performance requirements for JASO FC, FB; ISO-L-EGC and -EGB.
- Protects today's high-RPM, air-cooled 2-cycle engines against exhaust port blocking, combustion chamber and piston deposits, ring sticking and scuffing, and wear.
- Formulated with premium base oils and a low-ash additive package that provides excellent lubricity and detergency performance, surpassing the standard for preventing piston and combustion chamber deposits.
- Synthetic blend reduces exhaust smoke and prevents piston seizure and cylinder scuffing.
- Mixes readily with fuel for pre-mix type, even at low temperatures.
- Can be used in motorcycles, generators, lawnmowers, and handheld power equipment such as leaf blowers, trimmers, and chainsaws operating in hot, dirty, dusty environments and high loads for extended periods.
- JASO FD Certified.

APPLICATIONS



- Recommended for use in air-cooled, 2-cycle applications where an API TC, JASO FD, or ISO-L-EGD product is preferred. This oil supersedes previous JASO and ISO specifications.
- Can be used in either pre-mix or direct injection systems at fuel ratios up to 50:1.
- Do not use in engines requiring an NMMA® TC-W3® product.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES



Typical Properties for CITGO SUPERGARD Air-Cooled 2-Cycle Engine Oil:

Material Code	621611001
Gravity, ASTM D4052, °API	32.0
Density, lb/gal at 60°F	7.21
Flash Point, PMCC, ASTM D93, °F (°C)	185 (85)
Flash Point, COC, ASTM D92, °F (°C)	203 (95)
Viscosity ASTM D445	
cSt at 40°C	55
cSt at 100°C	8.5
Viscosity ASTM D2161	
SUS at 100°F	281
SUS at 210°F	54.8
Viscosity Index, ASTM D2270	129
Pour Point ASTM D97, °F (°C)	-49 (-45)
Appearance, Color	Purple
Sulfated Ash, ASTM D874, %	0.1
Total Base Number, ASTM D2896, mgKOH/g	2.2

CITGO and SUPERGARD are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.