



CITGO Jet Lubricant TM

OVERVIEW



- A quality, soap-thickened petroleum resin-based compound for use as a traction motor gear lubricant in heavy duty, high speed locomotive gear boxes.
- It provides an adhesive film that protects gears under heavy loads.

FEATURES & BENEFITS



- Formulated from petroleum resins to ensure good adhesion.
- Available in drums and one-pound polyethylene bags for ease of application.

APPLICATIONS



- Excellent for various open and closed gear cases and certain slow-moving open gears used throughout the industry.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES



Typical Properties for CITGO Jet Lubricant TM:

| Material Code | 655780001 |
|------------------------------------|-------------|
| Soap Type | Sodium |
| Texture | Tacky |
| Color | Dark Brown |
| Brookfield Viscosity, cP at 200°F | 6,500-8,000 |
| Timken OK Load, ASTM D2509, lbs | 40 |
| Four Ball EP Weld, ASTM D2596, kgf | 250 |
| Load Wear Index, ASTM D2596 | 38 |

CITGO is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.